PAVEMENT MARKING SCHEDULE

LOCATION STATION TO STATION	LENGTH	THERMOPLASTIC PAVEMENT MARKING -LINE 4"			THERMOPLASTIC PAVEMENT MARKING -LINE 12"		THERMOPLASTIC PAVEMENT MARKING -LINE 24"	THERMOPLASTIC PAVEMENT MARKING - LETTERS AND SYMBOLS	PAVEMENT MARKING REMOVAL	REMARKS
		WHITE SOLID	WHITE SKIP DASH 3' STRIPES ON 12' CENTERS	YELLOW SOLID	WHITE SOLID	YELLOW SOLID	WHITE	WHITE		
		FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	SQ FT	FOOT	
RUSHING DRIVE										
162+67.29 TO 163+87.59	120.30	240.6		481.2		26				
163+87.59 TO 165+22.59	135.00	270		540		30				
165+22.59 LT TO 165+54.67 LT	32.08	32.08								
165+22.59 RT TO 165+87.12 RT	64.53	64.53								
165+22.59 TO 166+37.59	115.00	115.00		230						
165+54.67 LT TO 166+62.73 LT	108.06	141.00								RADIUS OUTSIDE EDGELINE
165+60								20.6		ONLY & LT TURN ARROW
165+87.12 RT TO 166+56.11 RT	68.99	154.00								RADIUS OUTSIDE EDGELINE
166+16.11 RT TO 166+68.3 RT	52.19	334.00			71.7					SOUTH ISLAND
166+37.8 LT TO 166+66.88 LT	29.08	89.17			27					NORTH ISLAND
166+37.59							12			
IL 148										
59+95.81 LT TO 61+70.96 LT	175.15	350.30								
59+95.81 LT TO 66+11.53 LT	615.72								615.72	
61+70.96 LT TO 63+86.06 LT	215.10	215.10	53.78							
		2006	54	1251	99	56				
TOTALS	1731	3311			155		12	21	616	