

STANDARDS

INDEX OF SHEETS

SHT NO	DESCRIPTION
1	COVER SHEET
2	SIGNATURE SHEET
3	INDEX OF SHEETS, STANDARDS, MIXTURES REQUIREMENTS
4	GENERAL NOTES
5-8	SUMMARY OF QUANTITIES
9-11	TYPICAL SECTIONS
12-16	SCHEDULES OF QUANTITIES
17	TIE POINTS
18	GEOPAK ELEMENTS IDENTIFICATION
19	PLAN PROFILE - ROADWAY
20	PLAN PROFILE - DRAINAGE
21-22	PROPOSED REMOVAL AND CONSTRUCTION
23	EROSION CONTROL
24	RIGHT OF WAY
25-27	GEOMETRICS
28	PAVEMENT MARKINGS
29	DETAILS: INLET SPECIAL ; CAST IRON FRAME SPECIAL TYPE 1 WITH TYPE 1 CLOSED LID; CONCRETE COLLAR
30	DETAILS: UNEVEN LANES; ROUGH GROOVED SURFACE; SEEDING AND MULCHING, BUTT JOINT DETAIL
31-34	CROSS-SECTIONS RUSHING DRIVE
35-39	CROSS-SECTIONS IL 148
40-45	CROSS-SECTIONS SOUTH QUAD.
46-50	CROSS-SECTIONS NORTH QUAD.

000001-06	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-07	TEMPORARY EROSION CONTROL SYSTEMS
420001-07	PAVEMENT JOINTS
482001-02	HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT
482011-03	HMA SHOULDER STRIPS/SHOULDERS WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
542201-02	REINFORCED CONCRETE END SECTIONS FOR PIPE CULVERTS 15" THRU 36" DIA. SKEWED WITH ROADWAY
542301-03	PRECAST REINFORCED CONCRETE FLARED END SECTION
602601-03	PRECAST REINFORCED CONCRETE FLAT SLAB TOP
606001-05	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
606301-04	PC CONCRETE ISLANDS AND MEDIANS
701001-02	OFF-ROAD OPERATION, 2L, 2W, MORE THAN 15' FROM PAVEMENT EDGE
701006-05	OFF-ROAD OPERATION, 2L, 2W, 15' TO 24" FROM PAVEMENT EDGE
701101-04	OFF-ROAD OPERATION, MULTILANE, 15' TO 24" FROM PAVEMENT EDGE
701106-02	OFF-ROAD OPERATION, MULTILANE, MORE THAN 15' AWAY
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-03	LANE CLOSURE, 2L, 2W, MOVING OPERATIONS-DAY ONLY
701422-06	LANE CLOSURE, MULTILANE, FOR SPEEDS ≥ 45 MPH TO 55 MPH
701426-06	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER., FOR SPEEDS ≥ 45 MPH TO 55 MPH
780001-04	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATORS RAISED REFLECTIVE PAVEMENT MARKERS

MIXTURES REQUIREMENTS

Locations	Hot-Mix Asphalt Surface Course
Mixture Use(s):	Polymerized Hot-Mix Asphalt Surface Course, Mix D, N90
AC/PG:	SBS PG76-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture (Gradation)	IL-9.5mm
Friction	D Surface
Quality	QC/OA
Program:	

Locations	Hot-Mix Asphalt Base Course and Hot-Mix Asphalt Shoulders
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0mm Fine Grade
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture (Gradation)	IL-19.0mm Fine Grade
Friction	None
Quality	QC/OA
Program:	

FILE NAME :	USER NAME : #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, STANDARDS, MIXTURES REQUIREMENTS				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
c:\pwwork\pwwork\all\egko\0374570\7842\shs\cvr_sog_index.dgn		DRAWN -	REVISED -		726	(1-2) N-3	WILLIAMSON	50	3				
PLOT SCALE * (0.0, 0.000) 1/16"		CHECKED -	REVISED -		SCALE: SHEET NO. OF SHEETS STA. TO STA.				CONTRACT NO. 78402				
PLOT DATE * 3/20/2014		DATE -	REVISED -		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT								