

NOTES:

- 1. FOR DITCH BOTTOM PROTECTED BY EROSION CONTROL BLANKET, USE 400'(120m) SPACING. FOR SEEDED DITCH BOTTOM, USE 200'(60m) SPACING.
- 2. THIS WORK CONSISTS OF THE COMPLETE INSTALLTION OF EROSION CONTROL DITCH CHECK AT LOCATIONS AS SHOWN ON THE PLANS, OR AS DIRECTED BY THE ENGINEER. THE AGGREGATE GRADATION SHALL BE RR3 WITH A MINIMUM QUALITY OF CLASS B.

LOCATION				NUMBER		DITCH		
		SIDE	DITCH	OF DITCH	FORE	воттом	BACK	BERM
STATION	MEDIAN	LEFT	RIGHT	CHECKS	SLOPE	WIDTH	SLOPE	SLOPE
•	•							•

ESTIMATE QUANTITIES

	FORE SLOPE	DITCH BOTTOM	BACK SLOPE	BERM SLOPE	AGGREGATE DITCH CHECK EROSION CONTROL TON (METRIC TON)
MEDIAN DITCH	1:6	24(600)	_	1 : 10	95(86)
SIDE DITCH	1:6	24(600)	1:4	1 : 10 & 1 : 2	50(45)
SIDE DITCH	1:6	24(600)	1:4	1 : 2 & 1 : 2	19(17)
SIDE DITCH	1:4	24(600)	1:3	1 : 10 & 1 : 2	18(16)
SIDE DITCH	1:4	24(600)	1:3	1 : 2 & 1 : 2	14(13)

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches (millimeters) unless otherwise noted.

1-1-97 RENUM. A-12.04, NEW REVISION BOX, REVISED TITLE T.P.	03-15-12 CHANGED NOTE 1. R.D.			F.A.P SECT	ION COUNT	TY SHEETS	SHEET
BOX, ADDED QUANTITY CALCULATION BOX		STATE OF ILLINOIS	EROSION CONTROL AGGREGATE DITCH CHECK	317 (18)	I FULTO		34
9-15-05 REVISED DESIGNER NOTE M.A.		DEPARTMENT OF TRANSPORTATION				RACT NO. 6	68A25
10-16-06 REVISED RR3 QUALITY & TO 2007 SPEC. M.A.			NOT TO SCALE CADD STD. 280101-D4	FED. ROAD DIST, NO.	ILLINOIS FED. AID PROJECT		

30(750)

12(300)