



1. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE FOOT FOR CONCRETE STEPS, MEASURED ALONG THE TOP SURFACE AREA, WHICH SHALL INCLUDE ALL EXPANSION JOINTS, EPOXY COATED REINFORCEMENT BARS, AND CONCRETE SIDEWALK BETWEEN THE STEPS AND THE EXISTING CURB AND GUTTER. THE PROPOSED CONCRETE SIDEWALK BEHIND THE STEPS AND THE AGGREGATE BASE COURSE WILL BE PAID FOR SEPARATELY.

2. ALL CONCRETE STEPS AND ASSOCIATED SIDEWALK SHALL BE 4 FEET WIDE.

CONCRETE STEPS DETAIL



REINFORCED PORTLAND CEMENT CONCRETE SIDEWALK VARIABLE DEPTH DETAIL



THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE HOT-MIX ASPHALT SURFACE COURSE, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.


HOT-MIX ASPHALT RUN DOWN DETAIL STA. 26+00 TO STA. 26+50 AND STA 38+20 TO STA 39+03

DESIGNED - K.L.R. REVISED FILE NAME = p:\U0070062_Urbana - Main Street ITEP\Plans\shects\15-misc-details.dgm DRAWN - A.E.A. REVISED CHECKED - S.M.W. REVISED 3/7/2013 7:11:53 PW DATE - 03/2013 REVISED


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

COUNTY TOTAL SHEET NO. SECTION MISCELLANEOUS DETAILS 09-00483-01-RS CHAMPAIGN: 75 64 7124 MAIN STREET CONTRACT NO. 91480 SCALE : NONE SHEET NO. 64 OF 75 SHEETS STA. TO STA. FED. HOAD DIST. NO. ILLINOIS! FED. AL

- 1. WORK SHALL NOT START ON THIS ITEM UNTIL THE H.M.A. PAVING HAS BEEN COMPLETED.
- 2. PROTECTING AND PRESERVING SECTION OR SUBSECTION STONES AND OTHER MARKERS SHALL BE DONE IN ACCORDANCE TO SECTIONS 667 AND 668 OF THE STANDARD SPECIFICATIONS. DELETE REFERENCES TO BASIS OF PAYMENT.
- 3. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR SURVEY MARKER VALLT, WHICH PRICE SHALL INCLUDE ALL LABOR AND MATERIAL AS SPECIFIED INCLUDING PAYEMENT REMOVAL, MCHUMENT BOX, PLASTICIZED BLACK CONCRETE, AND FA-01/02 AGGREGATE, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED. SEE THE SPECIAL PROVISIONS FOR ADDITIONAL INFORMATION.



SURVEY MARKER VAULT DETAIL



- 1. ALUMINUM TABLET SHALL BE SET WITH A 5/8" X 48" REBAR.
- REFERENCING OF THE EXISTING SURVEY MARKER AND SETTING AND MARKING THE PROPOSED SURVEY MARKER SHALL BE DONE BY AN ILLINOIS PROFESSIONAL LAND SURVEYOR IN ACCORDANCE WITH SECTIONS 607 AND 668 OF THE STANDARD SPECIFICATIONS. DELETE REFERENCES TO BASIS OF PAYMENT.
- 3. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR PERMANENT SURVEY MARKERS (SPECIAL) WHICH PRICE SHALL INCLUDE ALL LABOR AND MATERIAL AS SPECIFIED, INCLUDING SETTING AND MARKING THE SURVEY MARKER BY AN ILLINOIS PROFESSIONAL LAND SURVEYOR, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.

PERMANENT SURVEY MARKER (SPECIAL) DETAIL

SPECIFICATIONS FOR ALUMINUM TABLET

SURVEY CAP FOR REBAR, 3-1/4-INCH CONVEX SURVEY CAP FOR 5/8-INCH REBAR WITH LETTERS RECESSED INTO THE SURFACE A MINIMUM OF CO.031 (1/32) INCH FOR EASY AND LONG-TERW LEGIBLITY, THE ALUMINUM CAP FOR REBAR SHALL BE PRODUCED BY THE PROCESS OF ORBITAL FORGING TO PRODUCE A HIGH-STRENGTH AND DURABLE MARKER CAP WHICH WILL NOT CHIP OR BREAK AND PROVIDE A SMOOTH FINISH FOR STAMPING OF DATA IN THE FIELD.

THE ALUMINUM CAP FOR REBAR SHALL BE TAPERED FOR A PERFECT COMPRESSION FIT. A SPECIAL PLASTIC INSULATOR SHALL BE INSTALLED TO PREVENT DISSIMILAR METAL CONTACT AND CORROSION, THE PLASTIC INSULATOR SHALL FORM READILY TO THE OUTER SHAPE OF THE REBAR AND TO THE INNER SHAPE OF THE ALUMINUM CAP SOCKET. THE PLASTIC INSULATOR SHALL BE LOW DENSITY POLYETHYLENE, A MINIMUM 1-1/2-INCH LONG AND CONFORM TO FEDERAL SPECIFICATION L-P 390.

COMPOSITION: STRENGTH: ELONGATION: SPECIFICATIONS: