F.A.U. RTE.	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.	
3887	(E-1, P, G	, н 8	k R)	RS-5	KANE	43	2
STA.	STA. + TO STA				+	+	
FED. RO.	AD DIST. NO.	1 1	LLIN	OIS	HIGHWAY	PROJECT	

INDEX OF SHEETS

- COVER SHEET
- INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
- SUMMARY OF QUANTITIES
- EXISTING & PROPOSED TYPICAL SECTIONS
- 10-18 ROADWAY & PAVEMENT MARKING PLANS
- 19-21 BRIDGE REPAIR PLANS
- 22-32 DETECTOR LOOP REPLACEMENT PLANS
- DETAILS FOR FRAMES & LIDS ADJUSTMENT WITH MILLING
- PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
- CURB OR CURB AND GUTTER REMOVAL & REPLACEMENT
- BUTT JOINT AND HMA TAPER DETAILS
- TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTION, AND DRIVEWAYS
- TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
- DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING
- DISTRICT ONE TYPICAL PAVEMENT MARKINGS
- TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
- ARTERIAL ROAD INFORMATION SIGN
- PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 1-800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).

THE MAXIMUM GRADE DIFFERENTIAL BETWEEN LANES SHALL NOT EXCEED 40MM (1-1/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES, THE CITY OF ELGIN, AND THE VILLAGE OF WEST DUNDEE.

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

THE RESIDENT ENGINEER SHOULD CONTACT MR. DON CHIARUGI, AREA TRAFFIC FIELD ENGINEERS, AT (847) 741-9857 OR (847) 715-8416 (CELL) PRIOR TO INSTALLING ANY PAVEMENT MARKING.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE ARTERIAL TRAFFIC CONTROL SUPERVISCR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS PRIOR TO MILLING AND/OR RESURFACING OPERATION.

THE RESIDENT ENGINEER SHALL MAKE ANY NECESSARY CHANGES TO DETECTOR LOOP QUANTITIES ACCORDINGLY, IF THERE ARE ANY CHANGES IN RESURFACING LIMITS.

LIMITS OF RESURFACING ON SIDE-STREETS THROUGH OUT THE IMPROVEMENT SHALL BE TO THE RADIUS OF RETURN, AS SHOWN ON THE PLANS, AND/OR AS DIRECTED BY THE ENGINEER.

ALL FINAL PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL, (TC-13).

ALL RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE PLACED IN ACCORDANCE WITH THE DISTRICT ONE "TYPICAL APPLICATIONS RAISED REFLECTIVE MARKER DETAIL," (TC-11).

STATE STANDARDS

000001-04 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

442201-02 CLASS C AND D PATCHES

604001-02 FRAME AND LIDS, TYPE 1

604086-01 FRAME AND GRATE, TYPE 23

701411-03 LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT

RAMP. FOR SPEEDS ≥ 45 MPH

701501-03 URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED

701601-04 URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH

NONTRAVERSABLE MEDIAN

701606-04 URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE

MEDIAN

701701-04 URBAN LANE CLOSURE, MULTILANE INTERSECTION

701801-03 URBAN LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK

OR SIDEWALK CLOSURE

702001-06 TRAFFIC CONTROL DEVICES

REVISIONS NAME DATE	ILLINOIS DEPARTMENT OF TRANSPORTATION				
	INDEX OF SHEETS, AND STATE	GENERAL NOTES, STANDARDS			
	SCALE: VERT. NATE 418/2007	DRAWN BY CHECKED BY			