


GENERAL NOTES


- 1. The marker shall be cast in place of Class SI Concrete.
- 2. Tie marker shall be installed after the final seeding has been completed unless otherwise specified by the Engineer.

TYPICAL APPLICATION

3. The tie distances to the section corner shall be measured and recorded by the IDOT Chief of Surveys.



PERMANENT SURVEY MARKERS



SECTION (11) RS-3

WOODFORD

BRONZE TABLET - No Scale TYPE I

(2) #15×1.2m

(#4x4') re-bars

-50(2) min.

250(10)

Class

'SI' Concret

mix

MARKER CAST IN PLACE

TYPE II

Ground line

.5m (5')

GENERAL NOTES

- 1. All type II markers shall be cast in place, and precast markers will not be allowed.
- 2. Two permanent magnets, each having a diameter of 19 $(\frac{3}{4})$ and a thickness of 6 $(\frac{1}{4})$, or equivalent. shall beattached to the underside of the tablet with an approved epoxy bonding agent.
- 3. The location of the markers shall be in accordance with the plans in general, the markers will be placed at the P.T.'s and P.C.'s of horizontal curves and spaces along the tangents in a way that a minimum of two markers are alway inter-visible, and not to exceed 300m(1000').
- 4. The markers shall be placed under the direction of the Engineer and shall be installed in a workmanlike manner in order that there will be no further settlement or horizontal shifting. The monuments shall be placed in a way that the survey point will fall within the portion of the plaque provided for that purpose.
- 5. The project designation, the centerline station, the survey point, and the elevation shall be permanently marked by the use of metal dies after marker has been installed.

All dimensions are in millimeters (inches) unless otherwise noted.

			ILLINOIS DEPARTMENT	OF TRANSPORTATION
			DISTRICT CAL	DD STANDARD
DATE	REVISIONS	BY	PERMANENT SURVEY TIE	
1-1-97	RENUM. D-3.01, NEW REVISION BOX	T.P.		
	ADD DESIGNER NOTE, REVISED TITLE BOX		l 8	k
7-7-98	ADD DESIGNER NOTE	J.A.		
5-24-06	REMOVED GEN. NOTE UNDER TIES	M.A.	PERMANENT SURVEY N	MARKERS TY.I - TY.II
~			CADD STD. NO. 667101-D4	
			SCALE: NOT DRAWN TO SCALE	DRAWN BY CADD
***************************************			DATE SEDATESS	CHECKED BY

DGN-ONLY

CHECKED BY 667101-D4

