

NOTES

Hollow structural sections shall conform to the requirements of ASTM designation A 500 Grade B Structural Steel Tubing and shall meet the longitudinal CVN requirements of 15 ft-lbs at 0° F.

All other steel shapes and plates shall conform to the requirements of AASHTO M 270 Grade 36 except posts and angles shall conform to AASHTO M 270, Grade 50.

Bolts, cap screws, and nuts shall conform to the requirements of ASTM designation A 307 except for high strength bolts, nuts and washers noted which shall conform to AASHTO M 164.

All bolts, nuts, cap screws, washers and lock washers shall be galvanized according to AASHTO M 232.

All posts, railing, rail splices, anchor devices and angles shall be galvanized after shop fabrication according to AASHTO M 111 and ASTM A 385. Galvanized rail shall not be painted.

Railing shall be according to Section 509 of the Standard Specifications, except as noted, and will be paid for at the contract unit price per foot for Steel Railings, Type SM.

All field drilled holes shall be coated with an approved zinc rich paint before erection.

For multi-span bridges, sufficient 1/4" x 6" x 1'-2" galvanized steel shims shall be provided to align rail between adjacent spans. Cost included with Steel Railings, Type SM.

The 1/4" high strength bolts used to connect the 6 x 4 x 3/4 angles to the post shall be tightened according to Article 505.04(1)(2) of the Standard Specifications. The 1" high strength bolts connecting the angles to the concrete shall be tightened to a snug fit and given an additional 1/8 turn. The 5/8" cap screws in bottom of posts shall be tightened to a snug fit only.


BILL OF MATERIAL

Item	Unit	Quantity
Steel Railings Type SM	Foot	420

* Threaded areas shall be plugged or blocked off during casting of beam. Galvanized after fabrication.

APR 05 2007 6:44 AM CW
L:\LOCK\DESIGN\2008\FINAL PLANS 070408\BRIDGE\R-34.DWG

REVISION	DATE



Drawn: R-34.DWG	Date: 04/06/07
LAYOUT: TWZ	10/12/06
DRAWN: RLA	10/12/06
REVIEWED: JUT	01/16/07

Phone: (309) 691-0902
Fax: (309) 691-1327
www.hanson-inc.com
Offices Nationwide

HANSON
Professional Services Inc.
2900 W. Willow Knolls Road
Peoria, Illinois 61614-1129

**TYPE SM STEEL BRIDGE RAIL
SIDE MOUNTED WITH
CONCRETE WEARING SURFACE**
LANCASTER RD. OVER LAMARSH CREEK
STRUCTURE NO. 072-3145
PEORIA COUNTY, ILLINOIS