HOT-MIX ASPHALT DESIGN TABLES - GRADE SEPARATION

LOCATION(S):	45TH STREET			
MIXTURE USE(S):	2 1/2" BINDER COURSE	1 3/4" SURFACE COURSE	LEVELING BINDER	8" SHOULDERS
PG:	PG64-22	PG64-22	PG64-22	PG58-22
RAP %:	15	0	0	30
(MAX)DESIGN AIR VOIDS:	4.0 % @ N50	4.0 % @ N50	4.0 % @ N50	2.0 % @ N30
MIXTURE COMPOSITION:	IL 19.0	N/A	N/A	B.A.M.
FRICTION AGGREGATE:	N/A	MIXTURE D	N/A	N/A

LOCATION(S):	42ND STREET			
MIXTURE USE(S):	8" BASE COURSE	2 1/2" BINDER COURSE	1 3/4" SURFACE COURSE	
PG:	PG64-22	PG64-22	PG64-22	
RAP %:	15	15	0	
(MAX)DESIGN AIR VOIDS:	4.0 % @ N50	4.0 % @ N50	4.0 % @ N50	
MIXTURE COMPOSITION:	IL 19.0	IL 19.0	N/A	
FRICTION AGGREGATE:	N/A	N/A	MIXTURE D	

		100566 DOADS #4 AND #0		
LOCATION(S):	ACCESS ROADS #1 AND #2			
MIXTURE USE(S):	8" BASE COURSE	2 1/2" BINDER COURSE	1 3/4" SURFACE COURSE	
PG:	PG64-22	PG64-22	PG64-22	
RAP %:	15	15	0	
(MAX)DESIGN AIR VOIDS:	4.0 % @ N50	4.0 % @ N50	4.0 % @ N50	
MIXTURE COMPOSITION:	IL 19.0	IL 19.0	N/A	
FRICTION AGGREGATE:	N/A	N/A	MIXTURE D	

HOT-MIX ASPHALT DESIGN TABLES - RAMPS

LOCATION(S):	BITUMINOUS SURFACE COURSE (AUXILIARY LANE AND I-57/I-64 INSIDE SHOULDER)
MIXTURE USE(S):	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX E, N105
AC/PG:	SBS PG76-22
RAP % (MAX):	0
DESIGN AIR VOIDS:	4.0 %, 105 GYRATION SUPERPAVE DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 9.5 mm OR IL 12.5 mm
FRICTION AGGREGATE:	E SURFACE

LOCATION(S):	BITUMINOUS SURFACE COURSE (RAMPS ONLY)			
MIXTURE USE(S):	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX D, N105			
AC/PG:	SBS PG76-22			
RAP % (MAX):	0			
DESIGN AIR VOIDS:	4.0 %, 105 GYRATION SUPERPAVE DESIGN			
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 9.5 mm OR IL 12.5 mm			
FRICTION AGGREGATE:	D SURFACE			

RTE. SECTION COUNTY TOTAL SHEETS NO. 57/64 (41-3)HBK JEFFERSON 518 U83 STA. TO STA.
FED. ROAD DIST. NO. | ILLINOIS | FED. AID PROJECT CONTRACT NO. 98963

HOT-MIX ASPHALT DESIGN TABLES - RAMPS CONTINUED

LOCATION(S):	BITUMINOUS BINDER COURSE & BITUMINOUS BASE COURSE (TOP LIFT)
MIXTURE USE(S):	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N105
AC/PG:	SBS PG76-22
RAP % (MAX):	0
DESIGN AIR VOIDS:	4.0 %, 105 GYRATION SUPERPAVE DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 19.0 mm
FRICTION AGGREGATE:	NONE

LOCATION(S):	BITUMINOUS BASE COURSE (LOWER LIFTS)
MIXTURE USE(S):	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N105
AC/PG:	PG64-22
RAP % (MAX):	10
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION SUPERPAVE DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 19.0 mm
FRICTION AGGREGATE:	NONE

LOCATION(S):	BITUMINOUS SHOULDERS, 8"
MIXTURE USE(S):	HOT-MIX ASPHALT SHOULDERS, SUPERPAVE
AC/PG:	PG58-22
RAP % (MAX):	50
DESIGN AIR VOIDS:	2.0 %, 30 GYRATION SUPERPAVE DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	BITUMINOUS AGGREGATE MIXTURE, SUPERPAVE
FRICTION AGGREGATE:	NONE

REVISIONS NAME DATE		ILLINOIS DEPARTMENT OF TRANSPORTATION			
TOWNE	DATE	HOT-MIX	ASPHALT	DESIGN	TABLES
		VETERANS MEMORIAL DRIVE			
		INTERCHANGE			
		SECTION (41-3)HBK			
		SCALE: NO SCALE		DRAWN	BY RLT
		DATE 3-22-07		CHECKE	D BY MTM