
NOTES

- 1. TYPE III BARRICADES AND ROAD CLOSURE SIGNS SHALL BE POSITIONED AS SHOWN, IN ACCORDANCE WITH HIGHWAY STANDARD B.L.R. 22-3 AND AS DIRECTED BY THE ENGINEER
- 2. TYPE A FLASHING WARNING LIGHTS SHALL BE USED ON EACH SIGN IN ADVANCE OF THE WORK DURING HOURS OF DARKNESS.
- 3. ALL WARNING SIGNS SHALL HAVE A BLACK LEGEND AND BORDER ON A FLUORESCENT ORANGE REFLECTORIZED BACKGROUND.
- 4. THE CONTRACTOR SHALL MAINTAIN ACCESS AT ALL TIMES AS DESCRIBED IN THE SEQUENCE OF CONSTRUCTION.
- 5. LONGITUDINAL DISTANCES MAY BE ADJUSTED TO FIT FIELD CONDITIONS.
- 6. ALL TYPE III BARRICADES UTILIZED FOR ROAD CLOSURES SHALL HAVE A LOW INTENSITY FLASHING LIGHT MOUNTED ON TOP OF EACH BARRICADE.
- 7. SPACE WARNING SIGNS APPROXIMATELY 500' APART UNLESS OTHERWISE SHOWN. EXACT LOCATION OF ALL WARNING SIGNS AND BARRICADES SHALL BE STAKED IN THE FIELD FOR APPROVAL BY THE ENGINEER PRIOR TO INSTALLATION.
- 8. ALL RESIDENTS FRONTING THE PROJECT SHALL BE NOTIFIED AT LEAST 48 HOURS PRIOR TO ROAD CLOSURES AFFECTING THEIR

LEGEND



☐ TYPE III BARRICADES STAGGERED W/ TYPE A LOW INTENSITY FLASHING LIGHTS

SIGN ON PORTABLE OR PERMANENT SUPPORT

ILLINOIS DEPARTMENT OF TRANSPORTATION TRAFFIC CONTROL GENERAL NOTES

VETERANS MEMORIAL DRIVE INTERCHANGE SECTION (41-3)HBK

SCALE:

DRAWN BY RLT CHECKED BY MTM

HANSON Servi

DATE 3-22-07