HANSON

EXTEND PARTIAL	PARALLEL TAXIWAY	ELECTRICAL LEGEND	
ω	Υ		

ELECTRICAL ABBREVIATIONS (CONTINUED)	
RCPT	RECEPTACLE
R	RELAY
\$	STARTER
SPD	SURGE PROTECTION DEVICE
SPST	SINGLE POLE SINGLE THROW
TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSOR
TYP	TYPICAL,
UG	UNDERGROUND
UGE	UNDERGROUND ELECTRIC
٧	VOLTS
W/	WITH
₩/0	WITHOUT
₩P	WEATHER PROOF
XFER	TRANSFER
XFMR	TRANSFORMER

**ELECTRICAL ABBREVIATIONS** 

ABOVE FINSHED FLOOR

AMERICAN WIRE GAUGE

AUTOMATIC TRANSFER SWITCH

AMPERES

Breaker

CONDUIT

CIRCUIT

CIRCUIT BREAKER

CONTROL RELAY COPPER

EMERGENCY

ENCLOSURE

GROUND

EXPLOSION PROOF

EMERGENCY STOP

ELAPSE TIME METER

HAND OFF AUTOMATIC

HORSEPOWER HIGH PRESSURE SODIUM

JUNCTION BOX

KILOWATTS

KILOVOLT AMPERE(S)

LIGHTING CONTACTOR

LIGHTING PANEL

MAIN CIRCUIT BREAKER

THOUSAND CIRCLUAR MIL

MAIN DISTRIBUTION PANEL

METAL HALIDE

MAIN LUGS ONLY

NORMALLY CLOSED

NORMALLY OPEN

NOT TO SCALE

OVERLOAD

PULL BOX PHOTO CELL

OVERHEAD ELECTRIC

POWER DISTRIBUTION BLOCK

MINIMUM

MAXIMUM

LIQUID TIGHT FLEXIBLE METAL CONDUIT (UL LISTED)

GROUND FAULT CIRCUIT INTERRUPTER GROUND FAULT INTERRUPTER

GALVANIZED RIGID STEEL CONDUIT HIGH INTENSITY DISCHARGE

DOUBLE POLE DOUBLE THROW

DOUBLE POLE SINGLE THROW

ELECTRICAL METALLIC TUBING

A, AMP

ATS AWG

BKR

C

CB

CKT

CR

CU DPDT

DPST

EMT

ENCL.

EP

ES

ETM

GFC)

GND

GRSC

HOA

HP

j

KVA

KW

LC

LTFMC

LP

MAX

MCB

MDP

MIN

MLO

NC

NO NTS

OHE

OL,

PB

PC

PNL

	AIRPORT EQUIPMENT ABBREVIATIONS
CCR	CONSTANT CURRENT REGULATOR
MIRL	MEDIUM INTENSITY RUNWAY LIGHT
MITL	MEDIUM INTENSITY TAXIWAY LIGHT
NDB	NON-DIRECTIONAL BEACON
PAPI	PRECISION APPROACH PATH INDICATOR
PLASI	PULSE LIGHT APPROACH SLOPE INDICATOR
REIL	RUNWAY END IDENTIFIER LIGHT
VASI	VISUAL APPROACH SLOPE INDICATOR
WC	WIND CONE

<u>NOTES</u>
--------------

- 1. ALL ELECTRICAL EQUIPMENT SHALL BE INSTALLED IN CONFORMANCE WITH NFPA 70 (MOST CURRENT ISSUE IN FORCE), THE RESPECTIVE EQUIPMENT MANUFACTURER'S DIRECTIONS AND ALL OTHER APPLICABLE LOCAL CODES, LAWS, ORDINANCES, AND REQUIREMENTS IN FORCE. ANY INSTALLATIONS WHICH VOID THE U.L. LISTING, ETL LISTING (OR OTHER THIRD PARTY LISTING) AND/OR THE MANUFACTURER'S WARRANTY OF A DEVICE WILL NOT BE PERMITTED.
- 2. CONTRACTOR SHALL COORDINATE WORK AND ANY POWER OUTAGES WITH THE RESPECTIVE FACILITY OWNER PERSONNEL AND THE AIRPORT MANAGER.
- 3. COLOR CODE PHASE AND NEUTRAL CONDUCTOR INSULATION FOR NO. 6 AWG OR SMALLER. PROVIDE COLORED INSULATION OR COLORED MARKING TAPE FOR PHASE AND NEUTRAL CONDUCTORS FOR NO. 4 AWG AND LARGER. INSULATED GROUND CONDUCTORS SHALL HAVE GREEN COLORED INSULATION FOR ALL CONDUCTOR AWG AND/OR KCMIL. STANDARD COLORS FOR POWER WIRING AND BRANCH CIRCUITS SHALL BE AS FOLLOWS:

120/240	VAC. 1	PHASE.	3	WIRE
PHASE A		BLACK		
PHASE B		RED		
NEUTRAL		WHITE		
GROUND		GREEN		

	CARLE TERMINATOR ALIX	
**	CABLE TERMINATOR/LUG	
<u> </u>	TRANSFORMER	
	DISCONNECT SWITCH	
_ \_	FUSIBLE DISCONNECT SWITCH	
	CIRCUIT BREAKER	
~~~	THERMAL MAGNETIC CIRCUIT BREAKER	
	FUSE	
<u></u>	TRANSIENT VOLTAGE SURGE SUPPRESSOR OR SURGE PROTECTOR DEVICE	
Ť	GROUND GROUND ROD, GROUNDING ELECTRODE, OR AT EARTH POTENTIAL	
¤	Indicating light	
$\Theta$	MOTOR	
•	LOAD, MOTOR, # = HORSEPOWER	
0	ELECTRIC UTILITY NETER BASE	
•	JUNCTION BOX WITH SPLICE	
xxx	EQUIPMENT, XXX = DEWCE DESCRIPTION	
GND	GROUND BUS OR TERMINAL	
S/N	NEUTRAL BUS	
	Panelboard with main lugs	
	PANELBOARD WITH MAIN BREAKER	
	fuse panel with main fuse pullout	
	DUPLEX RECEPTACLE 120V SINGLE PHASE GROUNDING TYPE	
	CONTROL STATION	
L SEM	Transfer switch	
	ENGINE GENERATOR SET	

	ELECTRICAL LEGEND - SCHEMATIC
	NORMALLY OPEN (N.O.) CONTACT
}K	NORMALLY CLOSED (N.C.) CONTACT
(\$*)	STARTER COIL, * = STARTER NUMBER
0. -#	OVERLOAD RELAY CONTACT
(RP)	CONTROL RELAY, * = CONTROL RELAY NUMBER
(P)	RELAY, * = RELAY NUMBER
~~	TOGGLE SWITCH / 2 POSITION SWITCH
OFF AUTO	2-POSITION SELECTOR SWITCH
HAND FAUTO	3-POSITION SELECTOR SWITCH (H-0-A SHOWN)
	2 POLE DISCONNECT SWITCH
17	3 POLE DISCONNECT SWITCH
-	PHOTOCELL,
-0-	TERMINAL BLOCK, * = TERMINAL NUMBER
	DEVICE TERMINAL, * == DEVICE TERMINAL NUMBER
-	INTERNAL PANEL WIRING
	FIELD WIRING
Ш	FUSE
GND	ground bus or terminal
S/N	NEUTRAL BUS
<u></u>	GROUND, GROUND ROD
0 0	INDUSTRIAL CONTROL RELAY OR LIGHTING CONTACTOR
CCR F S S S S S S S S S S S S S S S S S S S	S1 CUTOUT HANOLE REMOVED
CCR T N T P S	S1 CUTOUT HANDLE INSERTED
25.	N.O. THERMAL SWITCH
्रुः	N.C. THERMAL SWITCH

ECTRICAL LEGEND — SCHEMATIC .
KORMALLY OPEN (N.O.) CONTACT
ORMALLY CLOSED (N.C.) CONTACT
STARTER COIL, * = STARTER NUMBER
OVERLOAD RELAY CONTACT
Control relay, * = control relay number
relay, * = relay number
TOGGLE SWITCH / 2 POSITION SWITCH
2-Position selector switch
3Position selector switch (H-o-a shown)
POLE DISCONNECT SWITCH
POLE DISCONNECT SWITCH
HOTOCELL,
erminal block, * = terminal number
evice terminal, • = device terminal number
NTERNAL PANEL WIRING
IELD WIRING
USE.
ROUND BUS OR TERMINAL
EUTRAL BUS
ROUND, GROUND ROD
NOUSTRIAL CONTROL RELAY OR LIGHTING CONTACTOR
I CUTOUT HANDLE REMOVED
:1 CUTOUT HANDLE INSERTED
N.O. THERMAL SWITCH
n.c. Therwal Switch