SHEET NO. DESCRIPTION TITLE SHEET INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES SUMMARY OF QUANTITIES EXISTING AND PROPOSED TYPICAL SECTIONS ROADWAY AND PAVEMENT MARKING PLANS 13-166 DETECTOR LOOP REPLACEMENT PLANS DRIVEWAY DETAILS DISTANCE BETWEEN ROW AND FACE OF CURB < 15' (4.5M) DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT 20 21 BUTT JOINT AND HMA TAPER DETAILS 22 HMA TAPER AT EDGE OF P.C.C. PAVEMENT TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS. 23 INTERSECTIONS AND DRIVEWAYS TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS 25 DISTRICT ONE TYPICAL PAVEMENT MARKINGS TRAFFIC CONTROL AND PROTECTION AT TURN BAYS 26 (TO REMAIN OPEN TO TRAFFIC) PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

ARTERIAL ROAD INFORMATION SIGN

DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS

DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

(TO REMAIN OPEN TO TRAFFIC)

29

STANDARD NO. DESCRIPTION

000001 - 06 TYPICAL SYMBOLS, ABBREVIATIONS AND PATTERNS

442201-03 CLASS C AND D PATCHES

606001 - 04 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER

701101 - 02 . OFF-ROAD MOVING OPERATIONS. - MULTIGANE, 15' TO 24'

LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER, FOR SPEEDS =< 40 MPH

FROM

PAVT. EDGE

701606-08 URBAN LANE CLOSURE, MULTILANE, 2 W WITH MOUNTABLE MEDIAN

701701 - 08 URBAN LANE CLOSURE, MULTILANE INTERSECTION.

701801-05 LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE

701901 - 02 TRAFFIC CONTROL DEVICES

- 1. BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC. TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES, THE VILLAGE OF SKOKIE AND THE CITY OF EVANSTON.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.
- ANY PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.
- ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OR RAISED REFLECTIVE PAVEMENT MARKERS OUTSIDE THE REMOVAL LINE SHOWN ON THE PLANS SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.
- 6. BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY
- 7. ALL PAVEMENT PATCHING AND CURB AND GUTTER REMOVAL AND REPLACEMENT LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 8. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING
- THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.
- 10. THE RESIDENT ENGINEER SHALL CONTACT WALLY CZARNY, AREA TRAFFIC FIELD ENGINEER, AT (773) 685-4342 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.
- 11. THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.
- 12. ALL EXISITING DETECTOR LOOPS NOT SPECIFIED IN THE PLANS THAT ARE REMOVED DUE TO MILLING OPERATIONS SHALL BE REPLACED AND PAID FOR AT THE CONTRACT
- 13. EXISTING BROKEN FRAMES AND LIDS SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR AND SHALL BE REPLACED AS DIRECTED BY THE ENGINEER. REPLACEMENT FRAMES AND LIDS WILL BE PAID FOR ACCORDING TO ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS UNLESS A SEPARATE PAY ITEM HAS BEEN PROVIDED.
- 14. SAW CUTTING OF PAVEMENTS, CURB & GUTTER, ETC. SHALL BE TO FULL DEPTH AND SHALL RESULT IN A CLEAN STRAIGHT EDGE ON THE PORTION REMAINING. ALL SAW CUTTING SHALL BE CONSIDERED INCLUDED IN THE COST OF THE ITEM REMOVED.
- 15. DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS.
- DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.
- 17. PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKINGS ON ALL FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING
- WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC. THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).
- 19. BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE
- 20. UNLESS OTHER CONDITIONS WARRANT EXTENDED LANE CLOSURE AS DETERMINED AND APPROVED IN WRITING BY THE ENGINEER OR AS PROVIDED FOR IN THE CONTRACT SPECIFICATIONS, OVERNIGHT CLOSURES SHALL NOT BE ALLOWED FOR REHABILITATION PROJECTS INVOLVING DAYTIME MILLING AND RESURFACING OPERATIONS AND CLASS D PATCHING

TO STA.

INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES CHURCH ST. (GROSS POINT RD. TO DODGE AVE.) SCALE: SHEET NO. OF SHEETS STA.

ΔRev. COUNTY TOTAL SHEE NO. SECTION 1313 COOK (99B&0808)RS-1 CONTRACT NO. 60R99 ILLINOIS FED. AID PROJECT

FILE NAME =	USER NAME = rodriguezma	DESIGNED -	REVISED -
c:\pw_work\pwidot\rodriguezma\d0293791\0	127312-sht-gennote.dgn	DRAWN -	REVISED -
	PLOT SCALE = 100,0000 '/ in.	CHECKED -	REVISED ~
	PLOT DATE = 4/5/2012	DATE -	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**