

STA. TO STA. FED. ROAD DIST. NO. | ILLINOIS | FED. AID PROJECT

*(0102-683K, ETC&0507-635K)RS-1




*** REDUCE TO 40' (12 m) O.C. ON CURVES WITH POSTED OR ADVISORY SPEED 45 M.P.H. (70 km/h) OR LESS.


TWO-LANE/TWO-WAY




___ 3 @ 80' (24 m) O.C.



TWO-WAY LEFT TURN



MULTI-LANE/UNDIVIDED



MULTI-LANE/DIVIDED

3 @ 40′ (12 m) O.C.

GENERAL NOTES

- 1. MARKERS USED WITH DASHED LINES SHALL BE CENTERED IN THE GAP BETWEEN SEGMENTS.
- MARKERS USED ADJACENT TO SOLID LINES SHALL BE OFFSET 2 TO 3 (50 TO 75) TOWARD TRAFFIC AS SHOWN.
- MARKERS THROUGH TANGENTS LESS THAN 500' (150 m) IN LENGTH BETWEEN CURVES SHALL BE INSTALLED AT THE LESSER OF THE TWO CURVE SPACINGS.

LANE MARKER NOTES

- A. USE DOUBLE LANE LINE MARKERS SPACED AS SHOWN.
- B. REDUCE TO 40' (12 m) O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 10 M.P.H (20 km/h) LOWER THAN POSTED SPEEDS.

SYMBOLS

---- YELLOW STRIPE

── WHITE STRIPE

- ONE-WAY AMBER MARKER
- ONE-WAY CRYSTAL MARKER (₩/O) ◆ TWO-WAY AMBER MARKER

DESIGN NOTES

- 1. DOUBLE LANE LINE MARKERS SHALL BE USED UNLESS SPECIFIED OTHERWISE.
- 2. EXCEPT AS SHOWN ON THE LANE REDUCTION TRANSITION AND FREEWAY EXIT RAMP DETAIL, MARKERS ARE NOT TO BE SPECIFIED ON RIGHT EDGE
- 3. THE EXACT MARKER LIMITS, SPACING, AND COLOR SHOULD BE INCLUDED IN
- 4. MARKERS SHOULD NOT BE USED ALONGSIDE CURBS EXCEPT FOR EXTREMELY SHORT SECTIONS OF CURBS WHERE NOT MORE THAN TWO MARKERS WOULD BE

All dimensions are in inches (millimeters) unless otherwise shown.

	REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION		
	NAME	DATE	ILLINOIS DEFARTMENT OF TRANSPORTATION		
Τ.	RAMMACHER	09-19-94	TVD		ATTONIC
Τ.	RAMMACHER	03-12-99	TYPICAL APPLICATIONS		
Τ.	RAMMACHER	01-06-00	RAISED	REFLECTIVE	PAVEMENT
C.	JUCIUS	09-09-09			
			MARKERS	(SNOW-PLOW	RESISTANT)
			SCALE: NONE		DDAWN DV CADD
			SCALE: NONE		DRAWN BY CADD
					CHECKED BY

3 @ 80' (24 m) O.C. —

U \Rightarrow 40' (12 m) O.C. * SEE TWO-LANE/TWO-WAY WHERE MARKERS CONTINUE * * WHERE THE MEDIAN WIDTH IS 6' (2 m) OR LESS USE TWO-WAY MARKERS.

MINIMUM OF 3 W
EQUALLY SPACED

LEFT TURN