

NOTES:

T @ 2012 ENGINEERING ENTERPRISES INC

- 1. THE WIDTH OF THE FULL DEPTH PATCH OVER A TRENCH SHALL BE 12 (300) WIDER ON EACH SIDE OF THE TRENCH.
- 2. FOR METHOD OF MEASUREMENT AND BASIS OF PAYMENT, SEE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

SEQUENCE OF CONSTRUCTION (PATCHING FIRST)

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE WITH CLASS C OR D PATCH.
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.

SEQUENCE OF CONSTRUCTION (MILLING FIRST)

- 1. MILL HMA FIRST IF THERE IS AT LEAST 41/2 INCHES OR MORE OF HMA MATERIAL ON TOP OF THE EXISTING PAVEMENT OR IF THE PAVEMENT IS FULL DEPTH HMA. A MINIMUM OF 2 INCHES OF HMA MATERIAL SHALL BE IN PLACE AFTER MILLING.
- 2. REMOVE AND REPLACE WITH FULL DEPTH CLASS D PATCHES TO TOP OF MILLED SURFACE.

TO STA. N/A

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

441	consulting Engineers	USER NAME = bouerdl	DESIGNED -	F	R. SHAH	REVISED	-	A. ABBAS 04-27-98	
			DRAWN ~			REVISED	-	R. BORO 01-01-07	
		PLOT SCALE = 50.000 '/ IN.	CHECKED -			REVISED	-	R. BORO 09-04-07	
		PLOT DATE = 10/27/2008	DATE -	1	10-25-94	REVISED	-	K. ENG 10-27-08	

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

						T PATCH ACED P		
SCALE: NONE	SHEET	NO.	1	OF	1	SHEETS	STA.	N/A