



TYPICAL CROSSWALK MARKING




#### 4' (1.2 m) WIDE MEDIANS ONLY



DIAGONAL LINE SPACING: 50' (15 m) C-C (LESS THAN 30MPH (50 km/h))
75' (25 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h))
150' (45 m) C-C (MORE THAN 45MPH (70 km/h))

#### MEDIANS OVER 4' (1.2 m) WIDE




A MINIMUM OF TWO PAIRS OF TURN ARROWS SHALL BE USED, WHITE IN COLOR. ADDITIONAL PAIRS SHALL BE PLACED AT 200' (60 m) TO 300' (90 m) INTERVALS.



MEDIAN WITH TWO-WAY LEFT TURN LANE

## TYPICAL PAINTED MEDIAN MARKING





FULL SIZE LETTERS 8' (2.4 m) AND ARROWS SHALL BE USED.  $\P$  AREA = 15.6 SO. FT. (1.5 m<sup>2</sup>) (MLY AREA = 20.8 SO. FT. (1.9 m<sup>2</sup>)

\* TURN LANES IN EXCESS OF 400' (120 m) IN LENGTH MAY HAVE AN ADDITIONAL SET OF ARROW - "ONLY" INSTALLED MIDWAY BETWEEN THE OTHER TWO SETS OF ARROW - "ONLY".

TYPICAL LEFT (OR RIGHT) TURN LANE

## TYPICAL TURN LANE MARKING





# TYPICAL ISLAND MARKING

| •   |   |                         |   |  |
|---|---|-------------------------|---|--|
| TYPE OF MARKING   | WIDTH OF LINE   | PATTERN                 | COLOR   | SPACING / REMARKS  |
| CENTERLINE ON 2 LANE PAVEMENT   | 4 (100)   | SKIP-DASH               | YELLOW  | 10' (3 m) LINE WITH 30' (9 m) SPACE  |
| CENTERLINE ON MULTI-LANE UNDIVIDED PAVEMENT   | 2 @ 4 (100)   | SOLID                   | YELLOW  | 11 (280) C-C   |
| NO PASSING ZONE LINES:<br>FOR ONE DIRECTION<br>FOR BOTH DIRECTIONS                                | 4 (100)<br>2 © 4 (100)  | SOLID<br>SOLID          | YELLOW<br>YELLOW  | 5½ (140) C-C FROM SKIP-DASH CENTERLINE<br>11 (280) C-C<br>OMIT SKIP-DASH CENTERLINE BETWEEN  |
| LANE LINES  | 4 (100)<br>5 (125) ON FREEWAYS  | SKIP-DASH<br>SKIP-DASH  | WHITE<br>WHITE  | 10' (3 m) LINE WITH 30' (9 m) SPACE  |
| DOTTED LINES<br>(EXTENSIONS OF CENTER, LANE OR<br>TURN LANE MARKINGS)                             | SAME AS LINE BEING<br>EXTENDED  | SKIP-DASH               | SAME AS LINE BEING<br>EXTENDED                          | 2' (600) LINE WITH 6' (1.8 m) SPACE  |
| EDGE LINES  | 4 (100)   | SOLID                   | YELLOW-LEFT<br>WHITE-RIGHT                              | OUTLINE MOUNTABLE MEDIANS IN<br>YELLOW: EDGE LINES ARE NOT<br>USED NEXT TO BARRIER CURB  |
| TURN LANE MARKINGS  | 6 (150) LINE; FULL<br>SIZE LETTERS &<br>SYMBOLS (8' (2.4m))   | SOLID                   | WHITE   | SEE TYPICAL TURN LANE MARKING DETAIL   |
| TWO WAY LEFT TURN MARKING   | 2 @ 4 (100)<br>EACH DIRECTION   | SKIP-DASH<br>AND SOLID  | YELLOW  | 10' (3 m) LINE WITH 30' (9 m) SPACE FOR<br>SKIP-DASH; 5½ (140) C-C BETWEEN SOLID<br>LINE AND SKIP-DASH LINE  |
|   | 8' (2.4m) LEFT ARROW  | IN PAIRS                | WHITE   | SEE TYPICAL TWO-WAY LEFT TURN<br>MARKING DETAIL  |
| CROSSWALK LINES (PEDESTRIAN)<br>A. DIAGONALS (BIKE & EQUESTRIAN)<br>B. LONGITUDINAL BARS (SCHOOL) | 2 @ 6 (150)<br>12 (300) @ 45°<br>12 (300) @ 90°   | SOLID<br>SOLID<br>SOLID | WHITE<br>WHITE<br>WHITE                                 | NOT LESS THAN 6' (1.8 m) APART<br>2' (600) APART<br>2' (600) APART<br>5EE TYPICAL CROSSWALK MARKING DETAILS.   |
| STOP LINES  | 24 (600)  | SOLID                   | WHITE   | PLACE 4' (1.2 m) IN ADVANCE OF AND PARALLEL TO CROSSWALK, IF PRESENT. OTHERWISE, PLACE AT DESIRED STOPPING POINT. PARALLEL TO CROSSROAD CENTERLINE, WHERE POSSIBLE |
| PAINTED MEDIANS   | 2 @ 4 (100) WITH<br>12 (300) DIAGONALS<br>@ 45°<br>NO DIAGONALS USED FOR<br>4' (1,2 m) WIDE MEDIANS | SOLID                   | YELLOW:<br>TWO WAY TRAFFIC<br>WHITE:<br>ONE WAY TRAFFIC | II (280) C-C FOR THE DOUBLE LINE SEE TYPICAL PAINTED MEDIAN MARKING.   |
| GORE MARKING AND<br>CHANNELIZING LINES  | 8 (200) WITH 12 (300)<br>DIACONALS @ 45°  | SOLID                   | WHITE   | DIAGONALS:<br>15' (4.5 m) C-C (LESS THAN 30MPH (50 km/h))<br>20' (6 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h))<br>30' (9 m) C-C (OVER 45MPH (70 km/h))             |
| RAILROAD CROSSING   | 24 (600) TRANSVERSE<br>LINES; "RR" IS 6' (1.8 m)<br>LETTERS; 16 (400)<br>LINE FOR "X"               | SOLID                   | WHITE   | SEE STATE STANDARD 780001<br>AREA 0F:<br>"%"2-5.6 SO. FT. (0.33 m <sup>2</sup> ) EACH<br>"%"=54.0 SO. FT. (5.0 m <sup>2</sup> )                                    |
| SHOULDER DIAGONALS  | 12 (300) @ 45°  | SOLID                   | WHITE - RIGHT<br>YELLOW - LEFT                          | 50' (15 m) C-C (LESS THAN 30MPH (50 km/h))<br>75' (25 m) C-C (30 MPH (50 km/h) TO 45MPH (70 km/h))<br>150' (45 m) C-C (OVER 45MPH (70 km/h))                       |

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND STATE STANDARD 780001.

| LARGE SIZE  | SMALL SIZE  |
|-------------|---|
| 1.07 (11.5) | 0.60 (6.5)  |
| 1.47 (15.6) | 0.60 (6.5)  |
| 2.42 (26.0) | 1.37 (14.7)   |
| 0.33 (3.6)  | _   |
| 5.02(54.0)  |   |
| 0.56 (6.0)  |   |
|             | 1.07 (11.5)<br>1.47 (15.6)<br>2.42 (26.0)<br>0.33 (3.6)<br>5.02(54.0) |

All dimensions are in inches (millimeters) unless otherwise shown.

|  | LARGE SIZE  | SMALL SIZE  |
|--|-------------|-------------|
| THROUGH ARROW                                    | 1.07 (11.5) | 0.60 (6.5)  |
| LEFT OR RIGHT<br>ARROW                           | 1.47 (15.6) | 0.60 (6.5)  |
| COMBINATION<br>LEFT (RIGHT) AND<br>THROUGH ARROW | 2.42 (26.0) | 1.37 (14.7) |
| RAILROAD "R"<br>1.8m (6ft.)                      | 0.33 (3.6)  | _           |
| RAILROAD "X"<br>6.1m (20ft.)                     | 5.02(54.0)  |             |
| HANDICAPPED<br>SYMBOL                            | 0.56 (6.0)  |             |

| FILE NAME =                              | USER NAME = drivakosgn     | DESIGNED - EVERS | REVISED -T. RAMMACHER 10-27-94 | 94                           | DISTRICT ONE                                     | F.A. SECTION                  | COUNTY TOTAL SHEET SHEETS NO.   |
|--|----------------------------|------------------|--------------------------------|------------------------------|--|-------------------------------|---------------------------------|
| c:\pw_work\pwidot\drivekosgn\d0108315\te | l3.dgn                     | DRAWN -          | REVISED -C. JUCIUS 09-09-09    | STATE OF ILLINOIS            | TYPICAL PAVEMENT MARKINGS                        | 4307 11-00048-00-             | -RS WILL 15 12                  |
|  | PLOT SCALE = 50.000 '/ IN. | CHECKED -        | REVISED -                      | DEPARTMENT OF TRANSPORTATION |  | TC-13                         | CONTRACT NO. 63704              |
| 11025                                    | PLOT DATE = 9/9/2009       | DATE - 03-19-90  | REVISED ~                      |                              | SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA. TO STA. | FED. ROAD DIST. NO. 1 ILLINO' | IS FED. AID PROJECT M-9003(824) |