

B B

GREENE

SHEET NO. 1 OF 8 SHEETS

GENERAL NOTES

1. Concrete shall conform to the specification for Concrete Class SI as described in the Standard Specifications. Minimum 28 day compressive

2. Reinforcement bars shall conform to the requirements of ASTM A706

3. Reinforcement bars shall be clean and free of grease and scaling rust.

4. Reinforcement bar bending dimensions are out to out.

5. Porous Granular Backfill shall be placed behind all retaining walls. Material shall conform to Section 209 of the Standard Specifications except the coarse Aggregate Backfill shall be CA6 (Article 1004.05 c(4)). No backfill shall be placed until the concrete has attained its specified strength.

6. Porous Granular Backfill shall not be dumped into place. Backfill shall be placed by mechanical means.

7. It will be the Contractors responsibility to provide excavation protection to maintain limits of Structure Excavation as specified. If slopes are to be laid back, adequate benching detail shall be approved by the engineer. Earth backfill shall be brought up simultaneously with the Porous Granular Backfill. This work will be included in the contract unit price for Structure Excavation and no additional compensation will be allowed.

UNIT	WEST WALL	EAST WALL	TOTAL
Cu. Yd.	192.8	210	402.8
Cu. Yd.	629	555	1,184
Cu. Yd.	64.1	57.5	121.6
Lbs.	7,660	6,860	14,520
Foot	146	126	272
Foot	146	140	286
Sq. Yd.	87.73	85.23	172.96

TOTAL BILL OF MATERIAL

	RETAINING WALL								
GENERAL NOTES AND DETAILS									
	SECTION 10-00030-00-BT								
SANGAMON COUNTY									
-	F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.				
	*	10-00030-00-BT	SANGAMON	29	14				

	RTE.	SECTION	COUNTY	SHEETS	NO.
LS	*	10-00030-00-BT	SANGAMON	29	14
	· PLU	MMER BLVD MULTI-USE TRAIL	CONTRACT	NO.9 3	579
		ILLINOIS FED. A	ID PROJECT TE-0	OD6 (109)	