


ILLINOIS ROUTE 3

ILLINOIS ROUTE 156
(PARK STREET)

LEGEND

- ▲ SIGN, OR SIGNS
- TYPE II BARRICADE OR DRUM WITH FLASHING LIGHT
- ⊞ TYPE III BARRICADES
- ▨ AGGREGATE FOR TEMPORARY ACCESS



① W20-3(0)-48 (MODIFIED AS SHOWN, 48" x 48")

② M6-1(0) (30" x 18") OR M5-1L(0)

③ M6-1(0) (30" x 18") OR M5-1R(0)

④ R11-4 (60" x 30")

⑤ R3-5L

⑥

⑦

TYPE III BARRICADES & ④ ON EACH BARRICADE. INCLUDE FLASHING LIGHT ON EACH BARRICADE. STAGGER DURING STORM SEWER AND CURB CONSTRUCTION. ELIMINATE STAGGER FOR P.C.C. PAVEMENT CONSTRUCTION.

TYPE III BARRICADES & ④ ON EACH BARRICADE. INCLUDE FLASHING LIGHT ON EACH BARRICADE.

PLACE DRUM OR BARRICADE WITH LIGHT AT EACH INLET & LID THROUGHOUT THE STAGE (TYPICAL).

TYPE III BARRICADES & ④ ON EACH BARRICADE. INCLUDE FLASHING LIGHT ON EACH BARRICADE. FOR P.C.C. WORK ONLY.

SHOWING PLACEMENT OF DRUMS OR BARRICADES WITH LIGHTS AT 25' CTS. ADJOINING THE DAYTIME WORK AREA TO ALERT LOCAL TRAFFIC USING ENTRANCES ON THE WEST SIDE. SEE NOTE 4. THIS SHEET REGARDING LIGHTS.

SHOWING PLACEMENT OF DRUMS OR BARRICADES WITH LIGHTS AT 10' CTS. AROUND ALL EQUIPMENT AND OPEN EXCAVATION FOR NIGHTTIME. SEE NOTE 3 THIS SHEET REGARDING LIGHTS. THESE AREAS SHALL NOT BLOCK ENTRANCES AT THE END OF EACH DAY.

AT LIBRARY STREET TYPE III BARRICADES & ④ ON EACH BARRICADE. INCLUDE FLASHING LIGHT ON EACH BARRICADE.

NOTES

1. THE INITIAL PERIOD OF STAGE 2 SHALL ENTAIL INSTALLATION OF STORM SEWER AND SUBSEQUENT WORK SHALL NOT BEGIN UNTIL ALL STORM SEWER IS INSTALLED BETWEEN FOURTH AND THIRD STREETS, AS SHOWN. ALL EXCAVATION, CURB CONSTRUCTION AND P.C.C. PAVEMENT BETWEEN FOURTH AND THIRD STREETS, AS SHOWN, SHALL BE COMPLETED BEFORE STAGE 3 IS BEGUN.
2. TYPE II BARRICADES OR DRUMS WITH LIGHTS SHALL BE PLACED AT 25' CTS. ALONG EXCAVATED CURB AREAS AND FOLLOWING CURB CONSTRUCTION, THROUGHOUT, DURING THE INITIAL PERIOD OF THIS STAGE.
3. ALL TRENCHES AND EXCAVATIONS FOR DRAINAGE ITEMS SHALL BE BACKFILLED AND COMPACTED FLUSH WITH THE EXISTING SURFACE AT THE END OF EACH DAY'S OPERATION EXCEPT AT THE LOCATION WHERE WORK WILL CONTINUE THE FOLLOWING WORK DAY.
4. WHEN OBSTACLE OR EXCAVATION IS >100' IN LENGTH, LIGHTS SHALL BE STEADY BURN, OTHERWISE, LIGHTS SHALL BE FLASHING.
5. BARRICADES AND DRUMS SHOWN DO NOT REPRESENT THE FULL NUMBER REQUIRED TO DELINEATE NOTED AREAS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING THE NECESSARY NUMBER REQUIRED FOR THE PARTICULAR AREA.

FILE NAME = 6185-stage2.dgn	USER NAME = USERDESCR.	DESIGNED - HMG: CRW & EDW	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	CONSTRUCTION STAGING: STAGE 2			F.A. RTE. 9315	SECTION 06-00032-03-PV	COUNTY MONROE	TOTAL SHEETS 93	SHEET NO. 26
\\16185\water\local\moore\st\press\1\cadd\road	RAY\6185-stage2.dgn	DRAWN - HMG: CRW, EDW, & KOJ	REVISED -		SCALE:	SHEET NO. OF SHEETS	STA. TO STA.	FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT	CONTRACT NO. 97488		
PLOT SCALE = 3/8" = 1' / IN.	CHECKED - HMG: CRW	REVISED -	REVISED -									
PLOT DATE = 3/28/2012	DATE -	REVISED -	REVISED -									

HMG ENGINEERS, INC., 1075 LAKE ROAD, PO BOX 70, CARLYLE, IL 62231 PHONE (618) 594-3711 WWW.HMGENGINEERS.COM