
- 1. THE EXPOSED PORTION OF THE BOLLARD SHALL BE PAINTED YELLOW FROXY.
- 2. BOLLARD AND ASSOCIATED ITEMS ARE INCIDENTAL TO THE ELECTRIC SLIDING


BOLLARD DETAIL



GOOSENECK PEDESTAL DETAIL

SCALE: NONE

GOOSENECK PEDESTAL SHALL BE AMERICAN ACCESS SYSTEMS, INC. (7079 SOUTH JORDAN RD., UNIT 6, ENGLEWOOD, CO 80112, PHONE: 800-541-5677, FAX 303-799-9756) MODEL 18-001 OR APPROVED FOUAL.



NOTES

- EXISTING CARD READERS SHALL BE REMOVED. NEW CARD READERS SHALL BE FURNISHED & INSTALLED FOR GATE ENTRY/ACCESS.
- INCLUDE #12 AWG EQUIPMENT GND WIRE TO CARD READER.
- FACE OF CARD READER SHALL NOT EXTEND BEYOND BOLLARDS.

CARD READER ACCESS CONTROL UNIT PEDESTAL ELEVATION DETAIL


SCALE: NONE



<u>NOTES</u>


WARNING SIGNS/PLACARDS AS DETAILED ABOVE OR SIMILAR, SHALL BE INSTALLED WHERE CLEARLY VISIBLE ON BOTH SIDES OF EACH ELECTRIC SLIDE GATE. WARNING SIGNS SHALL BE WEATHERPROOF, CORROSION RESISTANT METAL, AS DETAILED ABOVE, AND IN ACCORDANCE WITH THE RESPECTIVE GATE MANUFACTURER'S RECOMMENDATIONS, HY-SECURITY PART NO. MX000882, OR EQUAL.

WARNING SIGN DETAIL



GATE OPERATOR FOUNDATION DETAIL 1

"NOT TO SCALE"



GATE OPERATOR FOUNDATION DETAIL 2

"NOT TO SCALE"

NOTES

- FOUNDATION FOR GATE OPERATOR SHALL BE 48" MIN. IN DEPTH AND OF THE LENGTH & WIDTH RECOMMENDED BY THE MANUFACTURER.
- COORDINATE CONDUITS INTO FOUNDATION.
- CONFIRM CONDUIT SIZES AND WIRING REQUIREMENTS WITH THE GATE OPERATOR MFR. ADJUST/INCREASE CONDUIT SIZES WHERE APPLICABLE. REQUIREMENTS VARY BETWEEN DIFFERENT MANUFACTURERS
- ALL ENCLOSURES RATED NEMA 4, 4X SHALL HAVE WATERTIGHT HUBS AT CONDUIT ENTRANCES U.L. LISTED NEMA 4, 4X FOR THE RESPECTIVE ENCLOSURE, TO MAINTAIN THE NEMA 4. 4X RATING.
- DETAIL NO. 1 ABOVE IS FOR GATE 1 (MAINTENANCE BLDG. GATE), GATE 5 (SOUTH T-HANGAR ACCESS GATE), & GATE 7 (FIRE STATIONS GATE).
- DETAIL NO. 2 ABOVE IS FOR GATE 2 (NORTH T-HANGAR ACCESS GATE) & GATE 3 (GAITROS AVIATION GATE).

DE074

ILLINOIS DECATUR,

HANSON Sprin Ph. (217)

CE FENCE READER, BOLLARD & OPERATOR DETAILS REPLAC PERIMETER F CARDI

36