
## LEGEND



## NOTES

- 1. CABLE FOR NEW HOMERUNS AND POWER CIRCUITS SHALL BE INSTALLED IN NEW 24-WAY PVC DUCT, NEW 4" DIRECTIONAL BORE OR NEW 2" DIRECT BURY PVC DUCT.
- 2. FOR CLARITY NO 2" PVC DUCTS HAVE BEEN SHOWN, HOWEVER THE CABLES CONTAINED WITHIN THEM HAVE BEEN SHOWN.

K:\ChampaignAp\\1105903\Draw\Sheets FILE: 1105903—E-0201.dwg UPDATE BY: Chris Groth PLOT DATE: 4/30/2012 3:49 PM

## UN051

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

NOTES

ර්

OVERVIEW

PROPOSED IMPROVEMENTS

WILLARD AIRPORT
UNIVERSITY OF ILLINOIS
NEW AIRFIELD LIGHTING VAULT

© CORVIGHT CRAWFORD, MURPHY & TILLY, IN CONDUITING EMBERS



DESIGN BY: KLB

DRAWN BY: CMT

CHECKED BY: CBG

APPROVED BY: CET

DATE: APRIL 20, 2012

JOB No: 11059-03

IL. PROJ. NO. CMI-4100 AIP PROJ. NO. 3-17-0016-XX

SHEET 17 OF 60 SHEETS