STATE STANDARD

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	INDEX OF SHEET, STATE STANDARDS AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4	EXISTING AND PROPOSED TYPICAL SECTIONS
5-8	ROADWAY AND PAVEMENT MARKING PLANS
9	DETAILS FOR FRAMES AND LIDS ADJUSTEMNT WITH MILLING
10	PAVEMENT PATCHING FOR BITUMINOUS SURFACED PAVEMENT
11	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
12	BUTT JOINT AND BITUMINOUS TAPER DETAILS
13	CITY OF CHICAGO CATCHBASINS, INLETS AND MANHOLE DETAILS
14	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS,
	INTERSECTIONS AND DRIVEWAYS
16	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
16	TEMPORARY INFORMATION SIGNING
17-18	CITY OF CHICAGO TYPICAL PAVEMENT MARKINGS

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR "CUAM" (CHICAGO UTILITY ALERT NETWORK), 312-744-7000 FOR FIELD LOCATIONS OR BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF CHICAGO.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (1-1/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V-H)

BUTT JOINT WILL BE INSTALLED AT THE END OF ALL RESURFACING (WHERE RESURFACING MEETS EXSTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINTS AND BITUMINOUS TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

ALL DRAINAGE STRUCTURES CLEANED AS PART OF THE CONTRACT MUST BE CLEANED AT THE COMPLETION OF THE CONTRACT AND AFTER RESURFACING OPERATIONS COMPLETION.

ALL WORK ON THE CONTRACT SHALL BE PERFORMED UTILIZING DAYTIME LANE CLOSURES.

CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD TECHNICIAN, AT 708) 597-9800 2 WEEKS PRIOR TO INSTALLING FINAL PAVEMENT MARKINGS

STD. NO. DESCRIPTION

000001-04 STANDARD SYMBOLS, ABBREVIATION AND PATTERNS

442201-01 CALSS C AND D PATCHES

606006 CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER

701101-01 OFF ROAD OPERATIONS, MULTILANE, LESS THAN 4.5 M (15') AWAY FOR SPEEDS >= 45 MPH

701301-02 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701606-04 URBAN LANE CLOSURE MULTI-LANE, 2W WITH MOUNTABLE MEDIAN

702001-06 TRAFFIC CONTROL DEVICES

780001-01 TYPICAL PAVEMENT MARKINGS

STATE STANDARD

PERMITS FROM THE DEPARTMENT OF SEWERS ARE REQUIRED FOR ALL UNDERGROUND STORM, SANITARY OR COMBINED SEWER SYSTME CONSTRUCTION, AND FOR ALL WORK INVOLVING ADJUSTJMENT OF SEWER STRUCTURES. THE DEPARTMENT OF SEWER'S PERMIT MUST BE OBTAINED BY A LICENSED SEWER CONTRACTOR/SUBCONTRACTOR MUST SUBMIT TWO SETS OF PLANS APPROVED BY THE DEPARTMENT OF SEWERS FOR THE ISSURE OF THE SEWER PERMIT TO SUITE 410, 333 SOUTH STATE STREET, CHICAGO, IL 60604-3971. INSPECTION WILL BE PROVIDED BY THE DEPARTMENT OF SEWERS.

IN CASE OF DAMAGE TO CITY OF CHICAGO SEWERS, PRIVATE AND PUBLIC DRAINS, SEWER STRUCTURES AND/OR BENCH MONUMENTS, THE CONTRACTOR SHALL IMMEDIATELY CONTACT THE DEPARTMENT OF SEWERS AT (312) 747-7892 OR (312) 747-7893

CLOSED LIDS SHALL BE PLACED ON ALL MANHOLES EXCEPT AT INTERSECTIONS, PERFORATED LIDS SHALL BE PLACED ON ALL CATCH BASINS.

THE RESIDENT ENGINEER AND THE CONTRACTOR SHALL FIELD-VERIFY THE CITY'S EXISTING SEWER FACILITIES IN THE LIMITS OF THE PREFERENCED PROJECT FOR ANY CONFLICTS DUE TO THE PROPOSED IMPROVEMENTS. ANY CONFLICT SHOULD BE RESOLVED WITH THE DEPARTMENT OF SEWERS PRIOR TO START OF CONSTRUCTIONS

BENCH MONUMENT LOCATIONS WITHIN THE LIMITS OF THE IMPROVEMENT CAN BE OBTAINED FROM THE DEPARTMENT OF SEWER AT SUITE 410, 333 SOUTH STATE STREET, CHICAGO, IL 60604-3971. THE CONTRACTOR IS RESPONSIBLE FOR THE COST OF REPLACING ANY BENCH MONUMENT DEMAGED OR DESTROYED DURING CONSTRUCTION.

SIDEWALK ACCESSIBILITY RAMPS SHALL NOT BE CONSTRUCTED DIRECTLY OVER EXISTING OR PROPOSED DRAINAGE STRUCTURES.

ALL BROKEN, CRACKED, WORN OR OTHERWISE DAMAGED OR BICYCLE UNSAFE FRAMES AND GRATES OR LIDS ON SEWER STRUCTURE SHALL BE REPLACED WITH NEW DEPARTMENT OF SEWERS STANDARD FRAMES AND GRATES OR LIDS. OLD FRAMES AND GRATES OR LIDS SHALL BE DELIVERED TO THE DEPARTMENT OF SEWERS AT 39TH AND ASHLAND AVENUE.

CITY OF CHICAGO WATER VALVE VAULTS AND SEWER STRUCTURES SHALL NOT BE CLOSED, COVERED OR OTHERWISE OBSTRUCTED DURING CONSTRUCTION WITHOUT WRITTEN PERMISSION FROM THE CITY OF CHICAGO DEPARTMENT OF WATER AND/OR DEPARTMENT OF

CURB AND GUTTER CONSTRUCTION SHALL PROVIDE A MINIMUM CURB HEIGHT OF 75 MM (3")

PAVEMENT REPLACEMENT AROUND FRAMES AND GRATES OR LIDS WHERE DRAINAGE, WATER MAIN OR ELECTRICAL STRUCTURES ARE ADJUSTED OR RECONSTRUCTED, SHALL BE WITH CLASS SI CONCRETE.

REVISIONS
NAME DATE

106 TH STREET
INDEX OF SHEETS, GENERAL
NOTES AND STATE STANDARDS

SCALE: VERT.
DATE

DATE

CHECKED BY

OT DATE = 3/31/2006 E. NAME = cityprojects/digil05\digil05co.m32 OT SCALE = 50.0000 '/ IN.

\projects\c1011CE\d1011C5ae.e62 3/31/206 2 47 1: Pk ||her=ayunsh