



NOTES:

1. CONES MAY BE SUBSTITUTED FOR TYPE I AND TYPE II BARRICADES DURING DAY OPERATIONS. CONES SHALL BE A MINIMUM OF 28" IN HEIGHT.
2. STEADY BURN LIGHTS WILL NOT BE REQUIRED FOR DAY OPERATIONS.
3. THE RAMP CLOSURE ADVANCE INFORMATION SIGNS SHALL BE ERRECTED IF THE CLOSURE TIME EXCEEDS TWENTY- FOUR (24) HOURS.
4. ADDITIONAL ADVANCE WARNING SIGNS ON EXIT GUIDE SIGNING WILL BE REQUIRED FOR EXIT RAMP CLOSURES THAT EXCEED TWENTY FOUR (24) HOURS IN LENGTH.

REVISIONS	
NAME	DATE
DWS	2-8
DWS	1/9
DWS	9/9
DWS	12/9
DWS/JAF	12/0
Revise devices to meet NCHRP 350	4/0

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES)  
UNLESS OTHERWISE SHOWN.

---

ILLINOIS DEPARTMENT OF TRANSPORTATION

### FREEWAY ENTRANCE AND EXIT RAMP CLOSURE DETAILS

02	SCALE: NONE
3	DATE 05/06/2003

DRAWN BY  
CHECKED BY  
TC-8