## INDEX OF SHEETS

COVER SHEET

INDEX OF SHEETS, STANDARDS,

COMMITMENTS, AND GENERAL NOTES

SUMMARY OF QUANTITIES

TYPICAL SECTION

TYPICAL SECTION (BRIDGE)

MISC. SCHEDULES

PLAN VIEW (REMOVAL)

PLAN VIEW

PAVEMENT MARKING

PLAN VIEW (S.N. 082-0207)

PLAN VIEW (S.N. 082-0166) 12-14 MISC. DETAILS

ELECTRICAL PLAN VIEW 15

## **STANDARDS**

482011-01 781001-02 701601-04 886001 701801-03 886006 702001-06 001006 780001-01

> COMMITMENTS NONE

egit welch help in a 100 of Wilder

CONTRACT NO. 76907 COUNTY TOTAL SHEET NO.
ST. CLAIR 15 2 RTE. SECTION \*\*

• FAP 582/FAU 9237 \*\* 82-3HB-1I, 82-3VB-1I

GENERAL NOTES

- 1) THE STANDARDS AND REVISION NUMBERS LISTED SHALL APPLY TO THIS PROJECT.
- 2) ILLINOIS STATE LAW REQUIRES A 48 HOUR NOTICE BE GIVEN TO UTILITIES BEFORE DIGGING. FIELD MARKING OF FACILITIES MAY BE OBTAINED BY CONTACTING JULLIE. OR FOR NON-MEMBERS, THE UTILITY COMPANY DIRECTLY. AGENCIES KNOWN TO HAVE FACILITIES WITHIN THE PROJECT AREA ARE AS FOLLOWS:

  - AMERENIP (GAS)
     AMERENIP (GAS)
     AMEREN-UE (ELECTRIC)
     CENTER POINT ENERGY (GAS TRANSMISSION)
     CHARTER COMMUNICATIONS, INC. (CABLE TV)
     ILLINOIS AMERICAN WATER CO. (WATER)
     MARATHON ASHLAND PIPELINE, LLC (PIPELINE)
     SBC (COMMUNICATIONS)

(MEMBERS OF J.U.L.I.E. (800) 892-0123 ARE INDICATED BY . NON-J.U.L.I.E. MEMBERS MUST BE NOTIFIED

- 3) "ROAD CONSTRCUTION AHEAD" SIGNS SHALL BE PLACED AT THE BEGINNING AND END OF THE PROJECT PLUS THE INTERSECTING SIDE ROADS, AND WILL BE CONSIDERED INCLUDED IN THE TRAFFIC CONTROL PAY ITEMS, ALL CONSTRUCTION SIGNS SHALL BE FLUORESCENT ORANGE.
- 4) ALL DIMENSIONS ARE IN FEET UNLESS OTHERWISE NOTED.
- 5) THE THICKNESS OF THE BITUMINOUS MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
- 6) WHERE SECTION OR SUB-SECTION MONUMENTS ARE ENCOUNTERED THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKERS AND MONUMENTS UNTIL THE OWNER, AN AUTHORIZED SUREYOR, OR AGENT HAS WITNESSED OR OTHERWISE REFERENCED THE LOCATION.
- 7) THE CONTRACTOR SHALL VERIFY ALL THE DIMENSIONS AND CONDITIONS IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- 8) SHORT TERM PAYEMENT MARKING SHALL BE APPLIED TO THE MILLED, PRIMED, BINDER, AND SURFACE COURSE, ONLY THE REMOVAL OF THE FINAL SURFACE APPLICATION WILL BE PAID FOR (WORK ZONE PAYEMENT MARKING REMOVAL SO FT). AN AMOUNT OF TEMPORARY PAYEMENT MARKING WHICH EQUALS THE AMOUNT OF PERMANENT PAYEMENT MARKING HAS ALSO BEEN ADDED TO THE PLANS.
- 9) THE ESTIMATED TONNAGE OF MILLED MATERIAL IS 6079.
- 10) TEMPORARY RAMPS SHALL BE PROVIDED AT THE BEGINING AND END OF THE RESURFACING SECTIONS (BUTT JOINTS) AND AT THE MILLING TRANSITIONS.
- 11) SAWCUTTING ON ALL EDGES FOR REMOVAL ITEMS SHALL BE INCLUDED IN THE COST OF THE REMOVAL ITEM AS INDICATED AND IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.
- 12) THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

## MIX REQUIREMENT CHART

MIXTURE USE	SURFACE	LEVELING BINDER	SHOULDER	TOP LIFT SHOULDER	
AC/PG	PG 70-22	PG 64-22	PG 58-22	PG 58-22	
RAP % (MAX)	10%	10%		30%	
DESIGN AIR VOIDS	4.0% @ Ndes=70	4.0% @ Ndes=70	2.0% @ Ndes=30**	2.0% @ Ndes=30**	
MIX COMPOSITION					
(GRADATION MIXTURE)					
FRICTION AGG	MIX "D"	MIX "C"	BAM	BAM	

\*\* TOP LIFT SHOULDER - DESIGN THIS MIX AT 2.0% VOIDS AND ADD ASPHALT TO REDUCE VOIDS TO 1.5%

PLAN QUANTITIES FOR BITUMINOUS CONCRETE SURFACE COURSE ITEMS ARE CALCULATED USING A WEIGHT OF 112 LB/SQ YD/IN (59.8 KG/SQ M/25MM THICKNESS).

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION		
NAME	DATE			
		INDEX OF HE	EETS, STANDARDS, AND GENERAL NOTES	
		COMMITMENTS	AND CENERAL NOTES	
		COMMITMENTS,	AND GENERAL NOTES	
		FAP 582/FAU 9237 (IL ROUTE 111) SECTION 82-3HB-1I. 82-3VB-1I		
		ST. CLAIR COUNTY		
		SCALE: VERT. HORIZ,	DRAWN BY	
			DICAMIN DI	
		DATE	CHECKED BY	