

TYPICAL BENCHING DETAIL FOR EMBANKMENT

NOTES:

- CONSTRUCT SUCCEEDING BENCH CUTS AND EMBANGMENT PLACEMENT AND COMPACTION FROM BOTTOM TO TOP IN STAIRSTEP FASHION.
- EXISTING FORESLOPE PREPARED IN ACCORDANCE WITH ARTICLE 205.04 OF THE STANDARD SPECIFICATIONS.
- BENCH CUT EXISTING SLOPE TYPICAL FOR EACH STEP.
- TRIM TO FINAL SLOPE.
- EQUAL 200 (8-INCH) LIFTS OF EMBANGMENT COMPACTED IN ACCORDANCE WITH ARTICLE 205.06 OF THE STANDARD SPECIFICATIONS.
- EXCAVATION OF BENCH CUTS WITHIN EXISTING EMBARKMENT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC METER OR CUBIC YARD FOR "EARTH EXCAVATION ESPECIALY". THIS PRICE WILL INCLUDE ALL LABOR AND MATERIAL NO ADDITIONAL COMPENSATION WILL BE ALLOWED.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF THANSPORTATION

BENCHING DETAIL FOR EMBANKMENT WIDENING

SCALES NOVE

DRAWN BY: CADD OECSED BY: SEB. BO-51

anna Maria (Braha P.

ACCORDANCE.