

DATE-TIME *DGN-SPEC* VI=BD32

F.A.U. RTE. 1693 SECTION COUNTY 05-00071-00-RS COOK 14 11 STA. TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT CONTRACT NO. 83848 PROP. BIT. OR P.C.C.

SURFACE REMOVAL - BUTT JOINT
9.0 m (30ft.) (NOIE "A") SAW CUT (INCLUDED IN THE COST OF BITUMINOUS SURFACE 4.5 m (15ft.) (NOTE "B") REMOVAL - BUTT JOINT) (NOTE "D") * * EXIST, PAVEMENT BUTT JOINT DETAIL TAPER LENGTH * * * VARIES PROP. BIT. SURF. CRSE. --PROP. BIT. BINDER CRSE. -* * EXIST. PAVEMENT BITUMINOUS TAPER DETAIL TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR RESURFACING ONLY $\mbox{\#}\mbox{\#}$ PC concrete, bituminous or bituminous resurfaced pavement. NOTES A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS. B: MINOR SIDE ROADS. C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING BITUMINOUS SURFACE. D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED BITUMINOUS COURSES. E: TAPER THE TEMP, RAMP AT A RATE OF 900 (3 ft.) PER INCH OF MILLING THICKNESS. F: INSTALLATION AND REMOVAL OF THE 1.35 m (4.5") TEMP. BIT. RAMP WILL BE PAID AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT". G: SEE ARTICLE 406,18 AND 406,24 OF THE STANDARD SPECIFICATIONS FOR "BITUMINOUS AND PCC SURFACE REMOVAL, BUTT JOINT". st see typical sections for milling thickness. \pm \pm \pm 6.1 m (20') PER 25 (1) RESURFACING (NOTE "A") 3.0 m (10') PER 25 (1) RESURFACING (NOTE "B") ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN. ILLINOIS DEPARTMENT OF TRANSPORTATION BUTT JOINT AND THE BUTT JOINT WILL BE PAID FOR PER SQUARE METER (SQUARE YARD.) AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT" OR AS "PORTLAND CEMENT CONCRETE SURFACE REMOVAL - BUTT JOINT". BITUMINOUS TAPER DETAILS

BD400-05 (VI=BD32)

DRAWN BY CHECKED BY

SCALE: NONE