

BRON7F" FOR DESIGNER NOTE: 1. ADD DISTRICT SPECIAL PROVISION. 2. MODIFIES STATE STD 667101 TO CALL

TABLET.

		CONTRAC	T NO.	88804
F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
669	11W-3,RS-8,*	TAZEWELL	442	329

TO STA.

*11BR-1,11BR-2

- 1. All type II markers shall be cast in place, and precast
- 2. Two permanent magnets, each having a diameter of 19 $(\frac{3}{4})$ and a thickness of 6 $(\frac{1}{4})$, or equivalent, shall beattached to the underside of the tablet with an approved epoxy bonding agent.
- 3. The location of the markers shall be in accordance with the plans in general, the markers will be placed at the P.T.'s and P.C.'s of horizontal curves and spaces along the tangents in a way that a minimum of two markers are alway inter-visible, and not to
- 4. The markers shall be placed under the direction of the Engineer and shall be installed in a workmanlike manner in order that there will be no further settlement or horizontal shifting. The monuments shall be placed in a way that the survey point will fall within the portion of the plaque provided for that purpose.
- 5. The project designation, the centerline station, the survey point, and the elevation shall be permanently marked by the use of metal dies after marker has

All dimensions are in millimeters (inches) unless otherwise noted.

		ILLINOIS DEPARTMENT OF TRANSPORTATION	
		DISTRICT CADD STANDARD	
REVISIONS	BY	PERMANENT SURVEY TIE	
ENUM. D-3.01, NEW REVISION BOX	T.P.	FERMANENT SURVET TIE	
DD DESIGNER NOTE, REVISED TITLE BOX		&	
ADD DESIGNER NOTE	J.A.	PERMANENT SURVEY MARKERS TY.I - TY.II	
		CADD STD. NO. 667101-D4	
		SCALE: NOT DRAWN TO SCALE DRAWN BY CADD	
		DATE \$\$DATE\$\$ CHECKED BY	
		667101-D4	