


FAU RTEs.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.
1547, 2757 01-00024-00-SW			COOK	24	20
STA. 09+99	)	Т	O STA. 112-	-83	
FED. ROAD	DIST. NO.	FED. AID I	PROJECT		
CONTRACT I	NO. 6344	1			



HOT-MIX ASPHALT MIXTURE REQUIREMENTS CHART						
MIXTURE TYPE	AIR VOIDS AT Ndes					
DRIVEWAYS						
HOT-MIX ASPHALT SURFACE COURSE, MIX 'C', N50 (IL 9.5), 1 1/2"	4% AT 50 GYR					
HOT-MIX ASPHALT BASE COURSE (HMA BINDER IL-19mm), 2 1/4"	4% AT 50 GYR					
PAVEMENT WIDENING						
POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "F", N90 (IL 9.5mm); 1 3/4"	4% AT 90 GYR					
HMA BASE COURSE (HMA BINDER IL-19mm); 6" (IN TWO LIFTS)	4% AT 90 GYR					

THE UNIT WEIGHT USED TO CALCULATE ALL HMA SURFACE MIXTURE QUANTITIES IS 112 LBS/SQ YD/IN

FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

REVISIONS DATE

NAME DATE

JMH PER REVIEW 02.26.10

ECC. PER REVIEW 05.11.10

JMH PER REVIEW 03.24.11

JMH PER REVIEW 03.24.11

LLINOIS DEPARTMENT OF TRANSPORTATION
VILLAGE OF JUSTICE
79th STREET & ROBERTS ROAD
SIDEWALK CONSTRUCTION
STREET RETURN, PIPE HANDRAIL,
& RETAINING WALL DETAILS

TE: 12/07/00

/09 CHECKE