
EXISTING TYPICAL SECTION MCCARTHY ROAD

STA 200+43 TO STA 211+33



PROPOSED TYPICAL SECTION MCCARTHY ROAD

STA 200+43 TO STA 211+33

EXISTING LEGEND

- HOT-MIX ASPHALT PAVEMENT, (AVG. DEPTH 5")
- PCC BASE COURSE, (10" & VARIES)
- С AGGREGATE BASE COURSE, (VARIES 6"-11")
- AGGREGATE SHOULDERS, VARIABLE DEPTH
- EXISTING DRIVEWAY

PROPOSED LEGEND

- HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50 2" (INCLUDED IN THE COST OF THE CLASS D PATCH)
- CLASS D PATCHES, TYPE IV. 15 INCH (PLACED IN 4 LIFTS)
- 3 AGGREGATE SHOULDERS, TYPE B-6" (INCLUDED IN THE COST OF THE CLASS D PATCH)
- 4 HMA SURFACE COURSE, MIX "C". N50-2"
- (5) HMA BASE COURSE, 6" (PLACED IN 2 LIFTS)
- AGGREGATE BASE COURSE, TYPE B, 8"

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

AIR VOIDS @ Ndes
4% @ 50 Gyr
4% @ 70 Gyr
44.
4% @ 50 Gyr
4% @ 50 Gyr

1. THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACES MIXTURE IS 112 LBS/SQ YD/IN. 2. THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22 AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS." FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

DESIGNED REVISED PER IDOT 5-19-10 REVISED REVISED CHECKED - TMS FILE - 100153-TypSec.sht 04/26/10

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

COUNTY TOTAL SHEETS NO. TYPICAL SECTIONS 1587 3098-T CONTRACT NO. 60K75 SCALE: NONE

OPYRIGHT © 2010, BY BAX TATE OF ILLINOIS - PROFE ICENSE NO. - 184-001121 - 1