

SEC. THRU ELLIPTICAL

RAIL SECTION

## ....

Splice must be

a slidina fit in

Rail Section.

SEC. THRU SPLICE

All Posts shall be normal to parapet.
All joints in rail shall be spliced per detail.
All exposed rail ends shall be capped per

Provide 1- $\frac{1}{8}$ " and 2- $\frac{1}{16}$ " Aluminum  $^{\circ}$  Shims for 25% of the Posts. Rail elements shall be parallel to Grade-high spots will be ground and low spots shimmed.

ALUMINUM RAILING, TYPE L
WHITEHALL AVENUE OVER
ADDISON CREEK
F.A. RTE. 4025
SECTION 09-00071-00-BR
COOK COUNTY
STATION 30+67.04
STRUCTURE No. 016-7618

	SHEET NO. S-9 SHEETS	F.A. SECTION						COUNTY	TOTAL SHEETS	SHEET NO.	
-		4025		09-00071-00-BR					COOK	31	21
									CONTRACT	NO. 63	437
		FED. R	OAD	DIST.	NO.	ILLINOIS	FED.	ΑII	) PROJECT		

BOTTOM RAIL

DESIGNED

CHECKED

CHECKED

DRAWN

RAIL SPLICE

ENGINEER OF BRIDGES AND STRUCTURES

FXAMINED

PASSED

200

TOP RAIL