



RIGHT ANGLE CROSSING

PAVEMENT TO BE FULL DEPTH ASPHALT, EXCEPT LIGHTLY USED PRIVATE CROSSING AND FARM CROSSINGS. THESE TYPE CROSSINGS ARE TO HAVE COMPACTED NS STANDARD SUB-BALLAST WITH 4" MAXIMUM ASPHALT.

WHERE HIGHWAY OR STREET HAVE SEPARATE SIDEWALKS, THE ENTIRE WIDTH OF CROSSING TO THE OUTSIDE EDGE OF SIDEWALK, WILL BE PAVED, WHERE PRACTICAL.

WHEN NECESSARY PROVIDE DRAINAGE BETWEEN TRACKS.

TO ALLOW FOR COMPACTION OF PAVING UNDER VEHICULAR TRAFFIC, THE SURFACE OF THE ASPHALT PAVING SHALL BE RAISED 3/8" ABOVE THE TOP OF THE RUBBER FLANGE WAYS FOR

IN FULL DEPTH CROSSINGS, LAY ASPHALT IN TWO LIFTS.

JAM STONE OR ASPHALT UNDER RUBBER FLANGE WAY BETWEEN TIES - BOTH FIELD AND GAUGE SIDES. FILL ALL VOIDS.

DESIGNED REVISED REVISED \$FILEL\$ CHECKED REVISED PLOT SCALE = \$SCALE\$ TENG & ASSOCIATES, INC.
ENGINEERS/ARCHITECTS/PLANNERS
PLOT DATE = \$DATE\$ DATE 06/04/10 REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** I-70 CONNECTION

NORFOLK SOUTHERN RAILWAY COMPANY HIGHWAY GRADE CROSSING ASPHALT PAVING WITH RUBBER FLANGE WAY

TOTAL SHEETS NO. SECTION COUNTY ST. CLAIR 285 107 998 82-2-1HVB CONTRACT NO. 76C44