

## **TEMPORARY DITCH CHECKS**

### PLACEMENT OF TEMPORARY DITCH CHECK IN DRAINAGE WAY



POINTS A SHOULD BE HIGHER THAN POINT B

### SPACING BETWEEN TEMPORARY DITCH CHECKS




L = THE DISTANCE SUCH THAT POINTS A AND B ARE OF EQUAL ELEVATION

B = THE LOW POINT IN CENTER OF CHECK

		REVISIONS	
		DRAWN	9-01-99
		REVISED	10-3-01
		RESIZED	5-8-08
STD. 9-	108	REVISED	05-04-10

## **SEEDING & MULCHING**



### GENERAL NOTES

IN GENERAL, ALL EARTH SURFACES DISTURBED DURING CONSTRUCTION OPERATIONS SHALL BE SEEDED AND MULCHED UPON COMPLETION OF ALL GRADING OPERATIONS.

FERTILIZER NUTRIENTS AND LIMESTONE SHALL BE APPLIED TO ALL SEEDED AREAS.


THE RATES OF APPLICATION OF FERTILIZER, MULCH AND LIME-STONE SHALL BE AS SPECIFIED IN THE SPECIAL PROVISIONS.

SECTIONS 250 AND 251 OF THE STANDARD SPECIFICATIONS SHALL GOVERN THIS WORK EXCEPT AS SPECIFIED HEREIN OR AS NOTED IN THE SPECIAL PROVISIONS.

	KEN1210N2		
	REDRAWN	2-15-89	
	REVISED	8-15-94	
	REVISED	6-3-99	
9-12	REVISED	3-27-08	

STD.


# TYPICAL CROSS SECTION SHOWING STEP CONSTRUCTION ON EXISTING FILL



MATERIAL TO BE REMOVED AND REPLACED IN THE EMBANKMENT IN ACCORDANCE WITH ART. 205.04 OF THE STANDARD SPECIFICATION. COST TO BE INCLUDED IN THE VARIOUS ITEMS OF EXCAVATION AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED BECAUSE OF THIS WORK.

> REVISIONS REDRAWN 2-15-89 REVISED 8-15-94 CHECKED 6-3-99 STD. 9-16

## TYPICAL LIMITS OF POROUS **GRANULAR EMBANKMENT AT 073-2007**



NOTE: POROUS GRANULAR EMBANKMENT WILL BE CA7 OR CA11 WITH THE TOP 1' CONSISTING OF CA6 OR CA10.

DESIGNED REVISED DRAWN REVISED PLOT SCALE = 50.0000 '/ IN. CHECKED REVISED DATE REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

SECTION COUNTY TOTAL SHEET NO. DETAILS: TEMP DITCH CHECKS; SEEDING AND MULCHING; STEP CONSTRUCTION PERRY ON EXIST FILL, TYP LIMITS OF POROUS GRANULAR EMBANKMENT CONTRACT NO. 78059 SHEET NO. OF SHEETS