

## STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



## INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nalling to wood forms or cementing to steel forms. (E) : Indicates epoxy coating.



alternatives.

	Mechanical coupler (E)
8++++++++++++++++++++++++++++++++++++++	34444444444444444
Reinforcement bar	

## STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required
		-

## NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength. All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers. See approved list of bar splicer assemblies and mechanical splicers for BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS STRUCTURE NO. 073-2007 TOTAL SHEET SHEETS NO. F.A.P. RTE. SECTION COUNTY SHEET NO.8 27 26 841 108B-1 PERRY CONTRACT NO. 78059 FED. ROAD DIST. NO. \_ ILLINOIS FED. AID PROJECT