INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
3,	SUMMARY OF QUANTITIES
4	EXISTING AND PROPOSED TYPICAL SECTIONS
5-31	EXISTING AND PROPOSED ROADWAY PLANS
32	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS
33-34	MULTI LANE FREEWAY PAVEMENT MARKING DETAILS
35	TRAFFIC CONTROL DETAILS FOR FREEWAY, SHOULDER CLOSURES AND PARTIAL RAMP CLOSURES
36	SIGNING FOR FLAGGING OPERATIONS AT WORK ZONE OPENINGS

LIST OF STATE STANDARDS:

STANDARD NO.	DESCRIPTION
000001-05	TYPICAL, SYMBOLS, ABBREVIATIONS, AND PATTERNS
701101 -02	OFF-ROAD OPERATIONS, MULTILANE, 15' (4.5m) TO 24" (600m FROM EDGE OF PAVEMENT
701400 <i>-03</i>	APPROACH TO LANE/CLOSURE, FREEWAY/EXPRESSWAY
701401- <i>05</i>	LANE CLOSURE, FREEWAY/ EXPRESSWAY
701411- <i>05</i>	LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMP, FOR SPEEDS > 45 MPH
701426 <i>-03</i>	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATIONS, FOR SPEEDS > 45 MPH
701901- <i>01</i>	TRAFFIC CONTROL DEVICES

GENERAL NOTES:

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE AT 800-892-0123 (OR 811) OR CUAN (CHICAGO UTILITY ALERT NETWORK), 312-744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION IS REQUIRED),

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF PEOTONE, MONEE AND UNIVERSITY PARK.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

THE RESIDENT ENGINEER SHALL CONTACT MS. CORA MATHIS, AREA TRAFFIC ENGINEER AT 815-485-6475 OR CONTACT THE EXPRESSWAY OPERATIONS SECTION AT 847-705-4151 TWO WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

SLURRY SEAL NOTE:

PRIOR TO APPLYING THE SLURRY SEAL MIXTURE, THE CONTRACTOR SHALL CLEAN THE PAVEMENT SURFACE BY REMOVING VEGETATION, LOOSE MATERIALS, DIRT, MUD AND OTHER OBJECTIONABLE MATERIALS.

APPLICATION RATE FOR SLURRY SEAL SINGLE PASS SHALL BE 20 LB/SQ YD (11 KG/SQ M).

SLURRY SEAL SHALL NOT BE APPLIED ON PCC SHOULDERS, IT SHALL BE OMITTED INSTEAD.

THE CONTRACTOR SHALL DEVISE AND SUBMIT A JOINT PLAN THAT MEETS THE APPROVAL OF THE ENGINEER.

EXPRESSWAY TEMPORARY STAGING NOTE:

THE CONTRACTOR IS REQUIRED TO PUT EPOXY PAVEMENT MARKING ON ALL TEMPORARY PAVEMENT SURFACES OVER THE WINTER MONTHS. WHEN THE FINAL PAVEMENT MARKINGS ARE INSTALLED, THE EPOXY THAT WAS PLACED FOR THE WINTER MONTHS IN TRANSITION AREAS ON EXISTING SURFACES SHALL BE REMOVED (BY GRINDING). PAVEMENT MARKING TAPE, TYPE III IS ONLY ALLOWED FOR TEMPORARY SEASONAL STAGING. THE CONTRACTOR MAY REQUEST PERMISSION TO PUT EPOXY IN PLACE OF TYPE III TAPE AT NO ADDITIONAL COST TO THE CONTRACT WHEN WEATHER CONDITIONS FALL OUTSIDE THE RESTRICTIONS STATED IN THE STANDARD SPECIFICATIONS FOR TYPE III TAPE.

FILE NAME =	USER NAME = steedpa	DESIGNED -	REVISED -
c:\pw_work\pwidot\steedpa\dØ142782\D175	09-sht-plan1.dgn	DRAWN -	REVISED -
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
	PLOT DATE = 6/1/2009	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES

I-57--KANKAKEE COUNTY LINE TO COOK COUNTY LINE

SCALE: SHEET NO. OF SHEETS STA. TO STA.

| SECTION | COUNTY SHEETS | NO. |
| TO TAL SHEETS | NO. |