

NOTES

- 1. TYPE III BARRICADES AND ROAD CLOSURE SIGNS SHALL BE POSITIONED AS SHOWN, IN ACCORDANCE WITH HIGHWAY STANDARD 701901 AND AS DIRECTED BY THE ENGINEER.
- TYPE A LOW INTENSITY FLASHING WARNING LIGHTS SHALL BE USED ON EACH SIGN IN ADVANCE OF THE WORK DURING HOURS OF DARKNESS.
- THE CONTRACTOR SHALL MAINTAIN ACCESS TO ENTRANCES AT ALL TIMES.
- 4. LONGITUDINAL DISTANCES MAY BE ADJUSTED TO FIT FIELD CONDITIONS.
- ALL TYPE III BARRICADES UTILIZED FOR ROAD CLOSURES SHALL HAVE A LOW INTENSITY FLASHING LIGHT MOUNTED ON TOP OF EACH BARRICADE.
- EXACT LOCATION OF ALL WARNING SIGNS AND BARRICADES SHALL BE STAKED IN THE FIELD FOR APPROVAL BY THE ENGINEER PRIOR TO INSTALLATION.
- ALL RESIDENTS FRONTING THE PROJECT SHALL BE NOTIFIED AT LEAST 48 HOURS PRIOR TO ROAD CLOSURES AFFECTING THEIR ACCESS.

LEGEND

- (1) W20-3(0)-48 (ROAD CLOSED AHEAD)
- TYPE 111 BARRICADES W/ R-11-2-4830 (ROAD CLOSED)
 SIGN AND TYPE A LOW INTENSITY FLASHING LIGHTS
- TYPE III BARRICADES W/ R-11-4-6030 (ROAD CLOSED TO THRU TRAFFIC) SIGN
- 4 W16-6pL(0)-2418
- 4
- 5 W16-6pR(0)-2418
- WORK ZONE

COUNTY TOTAL SHEET NO.

ST. CLAIR 55 9 SECTION DESIGNED -REVISED FILE NAME = USER NAME = maisingroser STATE OF ILLINOIS TRAFFIC CONTROL PLAN REVISED DRAWN 9274 04-00202-00-BR 27055-sht-staging.dgn **DEPARTMENT OF TRANSPORTATION** CONTRACT NO. 97369 PLOT SCALE = 40.0000 '/ IN. CHECKED -REVISED -SHEET NO. OF SHEETS STA. SCALE: TO STA. REVISED DATE PLOT DATE = 3/13/2009