STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION





BEAM ELEVATION (6 Required)

TOP OF BEAM ELEVATIONS*						
	Beam #1	Beam #2	Beam #3	Beam #4	Beam #5	Beam #6
Ç Brg. W. Abut.	478.91	478.91	478.96	478.91	478.75	478.59
E Brg. E. Abut.	478.44	478.46	478.46	478.32	478.04	477.74

*For fabrication only.





Notes:

- ① Load carrying components designated "NTR" shall conform
- to the Supplemental Requirements for Notch Toughness, Zone 2.
- (2) AASHTO M270 Grade 50 Steel.
- ${}^{3}_{4}$ " ϕ HS bolts, ${}^{15}_{16}$ " ϕ holes ð. Ã)
- Pipe and Pipe Roller Supports not shown for clarity. 5 All diaphragms shall be installed as steel is erected and secured with erection
- pins. Individual diaphragms at supports may be temporarily disconnected to install bearing anchor rods.
- Two hardened washers required for each set of oversized holes.
 Alternate C15 x 50 channels are permitted to facilitate material acquisition. Calculated weight of structural steel is based on the lighter section. The alternate, if utilized, shall be provided at no additional cost to the Department.
- (8) For detailed requirements for Pipe Roller Supports, see roadway plans and Special Provisions.
- (9) Sewer support system shall be detailed to maintain a constant flowline grade from back to back of abumtent. Contractor to coordinate all details and include with shop drawings for approval by the Engineer.