INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
- 3	SUMMARY OF QUANTITIES
4-11	TYPICAL SECTIONS
12-14	EXISTING AND PROPOSED ROADWAY PLAN
15-17	LOOP DETECTOR REPLACEMENT DETAILS
18	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
. 19	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
20	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
21	BUTT JOINT AND HMA TAPER DETAILS
22	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
23	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKINGS (SNOW-PLOW RESISTENT)
24	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
25	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMIAN OPEN TO TRAFFIC)
26	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
27	TEMPORARY INFORMATION SIGNING

LIST OF STANDARDS

000001-05 STANDARD SYMBOLS, ABBREVIATION AND PATTERNS

442201-03 CLASS C AND D PATCHES

604001-02 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER

604086-0/ FRAME AND LIDS TYPE 1

606001-03 FRAME AND GRATE TYPE 23

701501-04 URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED

701606-05 URBAN LANE CLOSURE, 2W WITH MOUNTABLE MEDIAN

701701-06 URBAN LANE CLOSURE, MULTILANE INTERSECTION

701901 TRAFFIC CONTROL DEVICES

886001 DETECTOR LOOP INSTALLATIONS

886006 TYPICAL LAYOUT FOR DETECTION LOOPS

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS & GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½INCHES (40 MM) WHERE THE SPEED LIMIT IS BOKM/H (45 MPH) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (Y:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT THETRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

THE RESIDENT ENGINEER SHALL CONTACT WALTER CZARNY, AREA TRAFFIC FIELD ENGINEER AT (773) 685-8386 AT LEAST (2) WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

FILE NAME =	USER NAME = auky	DESIGNED -	REVISED
c:\projects\d109498\design_aa.dgn		DRAWN	REVISED -
	PLOT SCALE = 103:8.461 '1' / IN.	CHECKED -	REVISED -
	PLOT DATE = 5/15/2008	DATE -	REVISED -

STATE	OF	ILLINOIS
DEPARTMENT (OF T	TRANSPORTATION

F.A.U. ROUTE 2746 (CUMBERLAND AVE.)				F.A.U. RTE.	SEC	TION	COUNTY	TOTAL	SHEET NO.	
INDEX OF SHEETS & PLAN NOTES					2746	3215	A-RS	СООК	27	2
MULA VI SHLEIS & FLAH HOILS						CONTRACT	NO.	50559		
SHEET NO. OF	SHEETS	STA.	TO S	STA.	FED. RC	DAD DIST. NO. 1	ILLINOIS FED. A	D PROJECT		