INDEX OF SHEETS

SHEET NO	DESCRIPTION
1	TITLE
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4	ALIGNMENT AND CONTROL POINTS
5	EXISTING CONDITIONS AND REMOVAL PLAN
6	PROPOSED ROADWAY PLAN
7	TRAFFIC CONTROL AND PROTECTION - STAGE 1
8	TRAFFIC CONTROL AND PROTECTION - STAGE 2
9	PAVEMENT MARKING PLAN
10	TEMPORARY TRAFFIC SIGNAL PLAN
11	TEMPORARY CABLE PLAN & TEMPORARY PHASE DESIGNATION DIAGRAM
12	TEMPORARY LIGHTING PLAN
13-15	TEMPORARY LIGHTING DETAILS
16	GENERAL PLAN AND ELEVATION
17	STAGE CONSTRUCTION DETAILS
18	TEMPORARY CONCRETE BARRIER
19	BEAM DETAILS 21"x36" DETAILS 1
20	BEAM DETAILS 21"x36" DETAILS 2
21	BEAM DETAILS 21"x48" DETAILS 1
22	BEAM DETAILS 21"x48" DETAILS 2
23	SUPERSTRUCTURE DETAILS 1
24	SUPERSTRUCTURE DETAILS 2
25	STEEL RAILING, TYPE SM
	WITH CONCRETE WEARING SURFACE AND CURB
26	PIER REPAIRS
27	NORTH & SOUTH ABUTMENT REPAIRS
28	NORTH AND SOUTH ABUTMENT
29	BAR SPLICER DETAILS
30	TYPICAL APPLICATIONS RAISED REFLECTIVE
	PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC-11)
31	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)
32	ARTERIAL ROAD INFORMATION SIGN (TC-22)

STATE	STANDARDS
000001 -05	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
420401 -06	BRIDGE APPROACH PAVEMENT
515001 - 02	NAME PLATE FOR BRIDGES
630001 <i>-0</i> 7	STEEL PLATE BEAM GUARDRAIL
630301 -04	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINAL
631032 - 03	TRAFFIC BARRIER TERMINAL, TYPE 6A
635006 -02	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011- 01	REFLECTOR MARKER AND MOUNTING DETAILS _
701201- 02	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS > 45 MPH
701301- 02	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701321 - 09	LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701901	TRAFFIC CONTROL DEVICES
704001 - 04	TEMPORARY CONCRETE BARRIER
857001	STANDARD PHASE DESIGNATION DIAGRAMS AND PHASE SEQUENCES
880001	SPAN WIRE MOUNTED SIGNALS AND FLASHING LIGHT BEACON INSTALLATION

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATIONS IS REQUIRED)
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OUTSIDE THE PAVEMENT MARKING LIMITS SHOWN ON THE PLANS SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.
- 5. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 6. THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TRAFFIC CONTROL DEVICES.
- 7. TWO WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS, CONTACT MS. CORA MATHIS,
 AREA TRAFFIC FIELD ENGINEER AT (815) 485-6475
- 8. CHANGEABLE MESSAGE SIGNS SHALL BE PLACED IN ADVANCE OF THE PROJECT LIMITS AT LEAST ONE WEEK PRIOR TO LANE CLOSURE AND TEMPORARY TRAFFIC SIGNAL OPERATIONS.

COMMITMENTS

NONE

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

OPERATIONS MIXTURE TYPE		AC TYPE	PERCENT AIR VOIDS
BRIDGE APPROACH	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 (IL-9,5mm), 2"	PG 64-22	'4% @ 70 GYR
(FLEXIBLE)	HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N70, 10" TO 13"	PG 64-22*	4% @ 70 GYR
TEMPORARY	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (IL-9.5mm), 1 1/2"	PG 64-22	4% @ 50 GYR
PAVEMENT	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N50, 8 1/2"	PG 64-22*	4% @ 50 GYR

THE UNIT WEIGHT USED TO CALCLATE ALL HMA SURFACE MIXTURE QUANTITIES IS 112 LBS/SQ YD/IN.

* WHEN RAP EXCEEDS 20%, THE NEW ASPHALT BINDER IN THE MIX SHALL BE PG 58-22.

	CG	Ciorba Group, Inc.	-
ŀ		CONSULTING ENGINEERS	Ł
		5507 North Cumberland Avenue, Suite 402 Chicago, Illinois 60656	1
		Tel. 773.775.4009 Fax 773.775.4014	1

- [USER NAME = jcoleman	DESIGNED	-	DMM	REVISED -	
٥.		DRAWN	-	DMM	REVISED -	
02	PLOT SCALE = 1.0000 '/ IN.	CHECKED	-	MJL	REVISED -	
14	PLOT DATE = 5/15/2008	DATE	-	05/13/2008	REVISED -	