INDEX OF SHEETS

STATE STANDARDS

SHE	ET NO.	DESCRIPTION		STANDARD NO.	DESCRIPTION
	1	TITLE SHEET		000001-05	TYPICAL SYMBOLS, ABBREVIATIONS AND PATTERNS
	2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES		442201 - 03	CLASS C AND D PATCHES
	3	SUMMARY OF QUANTITIES		482011- <i>03</i>	HMA SHLD. STRIPS/SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
	4-5	EXISTING AND PROPOSED TYPICAL SECTIONS		606001- <i>0</i> 3	CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER
	6-9	ROADWAY AND PAVEMENT MARKING PLANS		701011-01	OFF-ROAD MOVING OPERATIONS, 2L, 2W DAY ONLY
	10-12	DETECTOR LOOP REPLACEMENT PLANS		701201- <i>0</i> 2	LANE CLOSURE, 2L, 2W, DAY ONLY, ON-ROAD TO 600 MM (24")
	13	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT		701700 81	OFF-ROAD
	14	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT		701306-01	LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS - DAY ONLY
rida.	15	BUTT JOINT AND HMA TAPER	Age gains -	701501-04	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
	16	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS,		701901	TRAFFIC CONTROL DEVICES
		INTERSECTIONS AND DRIVEWAYS		886001	DETECTOR LOOP INSTALLATION
	17	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)		886006	TYPICAL LAYOUT FOR DETECTION LOOPS
	18	DISTRICT ONE TYPICAL PAVEMENT MARKINGS		i	
	19	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)			
	20	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGE	GING		
	21	ARTERIAL INFORMATION SIGNING			
	22	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN			
	23	DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING			

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 11/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SNOWN IN THE PLANS.

THE RESIDENT ENGINEER SHALL CONTACT MR. WALLY CZARNY, AREA TRAFFIC FIELD ENGINEER, AT (773) 685-8386 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

FILE NAME =	USER NAME = smithkl	DESIGNED -	REVISED -
c:\projects\d138408\sh_rdwy.dgn		DRAWN -	REVISED -
· · · · · · · · · · · · · · · · · · ·	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
	PLDT DATE = 5/22/2008	DATE -	REVISED -

DRIVEWAY DETAILS - DISTANCE BETWEEN ROW AND FACE OF CURB < 15'