<u> </u>	SUMMARY OF QUANTITIES			PAVEMENT	MARKINGS	SIGNS	LANDSCAPE	LIGHTS	SIGNALS	TRAINING		
						CO	STRUCTION	TYPE CODE				
S.I. (CODE NO.	PAY ITEM		UNIT	QUAN	1000	SFTY-1D	Y002~1C	Y003	Y030-1E	Y031	Y080
	25200650	SODDING, SALT TOLERANT (SPECIAL)		SQ YD	450	450						
	31101200	SUB-BASE GRANULAR MATERIAL, TYPE B 4"		SQ YD	4775	4775						
	40600100	BITUMINOUS MATERIALS (PRIME COAT)		GALLON	4499	4499						
	40600895	CONSTRUCTING TEST STRIP		EACH	2	2						
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT		SQ YD	780	780					1.74	
	40603340	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70		TON	3775	3775						
	42300300	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH		SQ YD	77.6	77.6						
	42400200	PORTLAND CEMENT CONCRETE SIDEWALK, 5 INCH		SQ FT	4720	4720						
	42400800	DETECTABLE WARNINGS		SQ FT	688	688						
	44000157	HOT-MIX ASPHALT SURFACE REMOVAL, 2"		SQ YD	44945	44945						
	44000200	DRIVEWAY PAVEMENT REMOVAL		SQ YD	119.6	119.6						
	44000500	COMBINATION CURB AND GUTTER REMOVAL		FOOT	1225.5	1225.5				l		
	44000600	SIDEWALK REMOVAL		SQ FT	4775	4775						
	44201749	CLASS D PATCHES, TYPE I, 9 INCH		SQ YD	46	46						
	44201753	CLASS D PATCHES, TYPE II, 9 INCH		SQ YD	166	166						
	44201757	CLASS D PATCHES, TYPE III, 9 INCH		SQ YD	37	37						
1	44201759	CLASS D PATCHES, TYPE IV, 9 INCH		SQ YD	580	580						
	60200105	CATCH BASINS, TYPE A, 4'-DIAMETER, TYPE 1 FRAME, OPEN LID		EACH	1	1						
	60249400	VALVE BOXES 6"		EACH	2	2						
	60250200	CATCH BASINS TO BE ADJUSTED		EACH	35	35					V 444	
	60250400	CATCH BASINS TO BE ADJUSTED WITH NEW TYPE 1 FRAME, OPEN LID		EACH	2	2						
	60252800	CATCH BASINS TO BE RECONSTRUCTED		EACH	1	1						
	60255500	MANHOLES TO BE ADJUSTED		EACH	24	24						
	60255800	MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID		EACH	2	2			1			
	60257900	MANHOLES TO BE RECONSTRUCTED		EACH	4	4						
	60266600	VALVE BOXES TO BE ADJUSTED		EACH	14	14						
1	60266910	VALVE BOXES TO BE REMOVED		EACH	2	2						
	60406000	FRAMES AND LIDS, TYPE 1, OPEN LID		EACH	2	2	ŀ					12 1
l	60500050	REMOVING CATCH BASINS		EACH	1	1						
	60603800	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12	ľ	FOOT	1225.5	1225.5						
	11.1.5.5.5.5	MOBILIZATION		L SUM	1223.3	1223.3						
1	67100100 70102620	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501		L SUM	1					· · · · · · · · · · · · · · · · · · ·		
		TRAFFIC CONTROL AND PROTECTION, STANDARD 701701		L SUM	' '	'						
	70102635	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801			1	'	l					
	70102640	SHORT-TERM PAVEMENT MARKING		L SUM		1	10000					
*	70300100	THERMOPLASTIC PAVEMENT MARKING — LETTERS AND SYMBOLS		FOOT	10000		10000				:	
*	78000100	THERMOPLASTIC PAVEMENT MARKING - LINE 4"		SQ FT	1472		1472					
*	78000200	THERMOPLASTIC PAVEMENT MARKING — LINE 6"		FOOT	20078		20078					
*	78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 12"		FOOT	2827		2827					
*	78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 24"		FOOT	2723		2723					
*	78000650	DETECTOR LOOP REPLACEMENT "	 -	FOOT	317		317					
	88600600	STAMPED ASPHALT CROSSWALK		FOOT	1304	1304		<u> </u>		1		
	XX005972	and the control of th		SQ.YD	112	112		. .		1		ł · · · · · · · · · · · · · · · · · · ·
	X4067107	POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50	:	TON	1770	1770						
	Z0000940	AGGREGATE FOR DRIVEWAY MAINTENANCE		TON	40	40						
	XX006947	HOT-MIX ASPHALT DRIVEWAY REMOVAL & REPLACEMENT		SQ YD	42	42				ļ		
$ldsymbol{ld}}}}}}$	42400430	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL		SQ FT	1240	1240		l	1	l		

* -	INDICATES	SPECIALTY	ITEMS
-----	-----------	-----------	-------

ETTO E	IDAD DIST. NO.	ILLINOIS	FED. AID PR	OWELL		
STA. TO STA.						
1621	08-00164-00)RS	COOK	11	02	
P. A. U. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO	

CONTRACT #63054

GENERAL NOTE

ROBINSON ENGINEERING SHALL BE NOTIFIED TWO (2) WORKING DAYS PRIOR TO CONSTRUCTION. CALL (708) 331-6700

THE CONTRACTOR SHALL PROVIDE AND INSTALL TWO (2) WEIGHTED SANDBAGS ON EACH TYPE I AND TYPE 2 BARRICADE USED. ONE (1) WEIGHTED SANDBAG SHALL BE INSTALLED ON EACH BOTTOM RAIL.

THE REMOVAL OF ANY DRIVEWAYS, PAVEMENT, CURB, ETC. SHALL BE ACCOMPLISHED BY MEANS OF A SAW CUT JOINT, AT THE DIRECTION OF THE ENGINEER. THIS WORK SHALL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE UNIT PRICE BID FOR THE VARIOUS REMOVAL ITEMS.

WHEN, IN THE CONSTRUCTION OPERATION, ANY LOOSE MATERIAL IS DEPOSITED IN THE FLOW LINE OF DITCHES, GUTTERS OR OTHER DRAINAGE STRUCTURES SO THAT THE NATURAL FLOW OF WATER IS OBSTRUCTED, IT SHALL BE REMOVED AT THE CLOSE OF EACH DAY BY THE CONTRACTOR AT HIS EXPENSE. AT THE CONCLUSION OF THE CONSTRUCTION OPERATIONS, ALL DRAINAGE STRUCTURES SHALL BE FREE FROM ALL DIRT AND DEBRIS. THIS WORK SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL J.U.L.I.E. AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, COMMUNICATIONS, AND GAS UTILITIES. (48 HOUR NOTIFICATION REQUIRED.)

IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

SCHEDULES INCLUDED IN THE PLANS HAVE BEEN PREPARED FROM FIELD NOTES. EXACT LOCATIONS FOR PATCHING SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.

AREAS DISTURBED BY CONSTRUCTION SHALL BE KEPT TO A MINIMUM. ALL AREAS DISTURBED UNNECESSARILY SHALL BE RESTORED AT THE CONTRACTORS EXPENSE.

UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF THE UTILITY INFORMATION.

ITEMS OF WORK LISTED IN THE SUMMARY OF QUANTITIES NOT SPECIFICALLY CALLED OUT ON THE PLANS SHALL BE PERFORMED AS DIRECTED BY THE ENGINEER.

ANY REFERENCE TO THE STANDARDS THROUGHOUT THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION.

THE NOMINAL THICKNESS OF HOT-MIX ASPHALT MIXTURE STATED IN THE SPECIFICATIONS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THINKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HOT-MIX ASPHALT SURFACE IS PLACED.

CONTRACTOR SHALL MILL EXISTING PAVEMENT PRIOR TO PATCHING.

ILLINOIS DEPARTMENT OF TRANSPORTATION

REVISIONS
NAME DATE
STREET RESURFACING
SUMMARY OF QUANTITIES & GENERAL NOTES

SCALE: VERT. NA HORIZ. 1*=50' DATE 05/07/08

DRAWN BY JZ

(708 CHECKED BY JP

ROBINSON ENGINEERING, LTD.
17090 SOUTH HAR AVENUE SOUTH HOLLAND BLADGE SOPT
(709) 331-5700 FRAN REGETTARTON NO. 184001138

LILNOS DESIGN FRAN REGETTARTON NO. 184001138

\ \