


CONTRACT NO. 95542



<u>NOTES</u>

- 1. Work this Sheet with Sheet 2 of 7 and Sheet 4 of 7.
- Formwork necessary for the wearing surface may be secured utilizing the bottom rail anchorage inserts and/or additional inserts cast into the beam. Drilling into the beam will not be permitted.
- 3. Reinforcement bars designated (E) shall be epoxy coated.
- 4. Bars indicated thus 31 x 2-#4 etc. indicates 31 lines of bars with 2 lengths per line.


MIN. BAR LAP


#4 = 1'-7"

SUPERSTRUCTURE BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	47	#4	30'-8"	C
a ₁ (E)	16	#4	31'-4"	C
b(E)	60	#4	32'-6"	
Reinfor Epoxy	L cement Coated	Pound	2,610	
Surface		Sq. Yd.	212	
Protect	ive Coa	Sq. Yd.	212	
Bridge	Deck G	Sq. Yd.	212	

DECK PLAN





CUTTING DIAGRAM Order bars full length. Cut bars as shown and use remainder at other end of span.

C	ONCRI	ETE	WEARING	SURFAC	E DE	TAILS
Date	Designed	MJP	CS #900 (H	ARRY LAND ROA	D)	Sheet No.
Revisions	Designed	וטועו	OVER TRIB.	OVER TRIB. TO LAKE DECATUR		
	Drawn	BKN	SECTION (SECTION 05-00205-00-BR		
	Checked	KWB		MACON COUNTY STA. 15+93.29		
	Approved	KWB	•	R. NO. 058-3386		of 7
Prepared by:	URS		East Ash Avenue tur, II. 62526	- почетов поделения почетов в поделения в поделения в поделения в почетов в почетов в почетов в почетов в поче Почетов в почетов в		URS Job No. 36431928