

STRUCTURE GEOTECHNICAL REPORT

I-39 and US 20 Noise Abatement Wall 20
(I-39 Reconstruction)
Proposed SN-101-N7009



03/08/2024

FAI 39 & FAP 301
WINNEBAGO COUNTY, ILLINOIS
JOB NO. D-92-064-19
PTB 193-020
KEG NO. 19-1138.00

Authored By:

Matt Masterson, P.E. &
Michael Harden, E.I.

mmasterson@kaskaskiaeng.com

(618) 233-5877

Prepared For:

Alfred Benesch & Company
35 W Wacker Drive
Chicago, IL 60601

March 8, 2024



TABLE OF CONTENTS

1.0	PROJECT DESCRIPTION AND SCOPE.....	1
1.1	Introduction.....	1
1.2	Project Description.....	1
1.3	Proposed Structure Information	1
2.0	FIELD EXPLORATION	1
2.1	Subsurface Exploration and Testing	1
2.2	Subsurface Conditions.....	1
	Table 2.2.1 - Boring Information Summary.....	2
	Table 2.2.2 – Subsurface Profile Summary	2
2.3	Groundwater	3
3.0	GEOTECHNICAL EVALUATIONS	3
3.1	Settlement	3
3.2	Seismic Considerations	3
	Table 3.2.1 - Summary of Seismic Parameters	3
4.0	FOUNDATION EVALUATIONS AND DESIGN RECOMMENDATIONS	3
4.1	Foundation Recommendations	3
	Table 4.1.1 - Summary of Foundation Recommendations.....	4
4.2	Lateral Pile Response.....	6
	Table 4.2.1 - Soil Parameters for Lateral Pile Load Analysis	7
	Table 4.2.2 - Rock Parameters for Lateral Pile Load Analysis	7
5.0	CONSTRUCTION CONSIDERATIONS.....	8
5.1	Construction Activities.....	8
5.2	Temporary Sheet piling and Soil Retention.....	8
5.3	Site and Soil Conditions.....	8
6.0	COMPUTATIONS.....	8
7.0	GEOTECHNICAL DATA.....	8
8.0	LIMITATIONS.....	8

EXHIBITS

- Exhibit A - Location Map
- Exhibit B - Boring Plan
- Exhibit C - General Plan and Elevation Plan (GP&E)
- Exhibit D - Boring Logs
- Exhibit E – Subsurface Profile
- Exhibit F - Foundation Analysis

1.0 PROJECT DESCRIPTION AND SCOPE

1.1 Introduction

The geotechnical study summarized in this report was performed by Kaskaskia Engineering Group, LLC (KEG) for proposed Noise Wall 20 adjacent to I-39. The project is located in Winnebago County, Illinois. The purpose of this report is to document subsurface geotechnical conditions, provide analyses of anticipated site conditions as they pertain to the project described herein, and to present design and construction recommendations for the proposed structure.

1.2 Project Description

The project consists of placing a noise abatement wall along west IL-20 access ramp to I-39. The general location of the proposed structure is shown on a Location Map, Exhibit A. The project is located southeast of Rockford, IL.

1.3 Proposed Structure Information

The proposed structure will consist of one noise abatement wall. The wall will be 20 ft. tall and measure 1,811 ft. 5 1/8" long from approximately Station 69+11.46 to Station 87+20.69. A General Plan and Elevation Plan (GP&E) is included in Exhibit C.

Further substructure details will be based on the findings of this SGR.

2.0 FIELD EXPLORATION

2.1 Subsurface Exploration and Testing

Nine standard penetration test (SPT) borings were drilled by the Illinois Department of Transportation (IDOT) District 2 in May of 2023. The boring locations are shown on the Boring Plan, Exhibit B. Detailed information regarding the nature and thickness of the soils encountered and the results of the field sampling and laboratory testing are shown on the Boring Logs, Exhibit D. A Soil Profile is included as Subsurface Profile, Exhibit E.

2.2 Subsurface Conditions

The profiles at the nine (9) boring locations exhibited layers of silty clay loam, clay loam, sandy loam, sandy clay loam, loam, sandy clay loam till, clay loam till, silty sand, sand, and silty loam. Bedrock was encountered in four (4) borings (B-6, B-7, B-8, and B-9) and consisted of tan weathered limestone at around El. 818 ft. Table 2.2.1 shows a summary of depth of drilling, the top of rock, and ground surface elevation (GSE) of the borings. A summary of the general condition of the subsurface is described in Table 2.2.2.

Table 2.2.1 - Boring Information Summary

Designation	Depth (ft)	Top of Rock (ft.)	GSE (ft.)
B-1	21	-	869.64
B-2	21	-	866.57
B-3	16	-	857.37
B-4	21	-	851.67
B-5	16	-	841.30
B-6	13.5	824.6	836.60
B-7	6	825.1	829.55
B-8	5	816.1	820.59
B-9	7.5	809.5	816.54

Table 2.2.2 – Subsurface Profile Summary

Soil Type	N-Values (bpf)	Q _u (tsf)	WC (%)	Boring
Silty Clay Loam	7 - 14	0.4 - 2.3	11 – 21	B-1, B-3, B-4, B-5, B-6, B-7
Clay Loam	8 - 22	1.3 – 3.1	15 – 20	B-1, B-4, B-5
Sandy Loam	8 – 62	-	7 – 19	B-1, B-4, B-5, B-6, B-8, B-9
Sandy Clay Loam	9 - 34	-	9 – 21	B-1, B-2, B-3, B-4, B-5, B-7
Loam	-	-	15	B-2
Sandy Clay Loam Till	11 – 26	-	12 – 13	B-2, B-4
Clay Loam Till	-	-	-	B-1
Silty Sand	9	-	12 – 16	B-4
Sand	11	-	17	B-5, B-6
Silty Loam	6 - 16	-	17 – 24	B-5, B-6, B-9

2.3 Groundwater

Groundwater was not encountered during drilling. It should be noted that the groundwater level is subject to seasonal and climatic variations. In addition, without extended periods of observation, measurement of true groundwater levels may not be possible.

3.0 GEOTECHNICAL EVALUATIONS

3.1 Settlement

Since no significant grading or changes to the existing grade level are expected, it is estimated that no settlement will be experienced. Therefore, no settlement calculations were performed for the proposed structure.

3.2 Seismic Considerations

The determination of Seismic Site Class was based on the method described by IDOT AGMU Memo 09.1 - Seismic Site Class Definition and the IDOT provided spreadsheet titled: '*Seismic Site Class Determination*.' Using these resources, the controlling global site class for this project is Soil Site Class C.

Additional seismic parameters were calculated for use in the design of the structure. Published information and mapping from the USGS, including software directly applicable to the AASHTO Guide Specifications for LRFD Seismic Bridge Design, was used to develop the parameters for the bridge location. The values, based on Soil Site Class C, are summarized below.

Table 3.2.1 - Summary of Seismic Parameters

Parameter	Value
Soil Site Class	C
Spectral Response Acceleration, 0.2 Sec, S_{DS}	0.102 g (Site Class C)
Spectral Response Acceleration, 1.0 Sec, S_{D1}	0.056 g (Site Class C)
Seismic Performance Zone	1

As indicated in the table above, the Seismic Performance Zone is 1, based on S_{D1} and Table 3.15.2-1 in the IDOT Bridge Manual, the Soil Site Class C, and Figure 2.3.10-4 in the IDOT Bridge Manual.

4.0 FOUNDATION EVALUATIONS AND DESIGN RECOMMENDATIONS

4.1 Foundation Recommendations

The foundations supporting the proposed walls should be sufficient to resist the dead and dynamic loads. For the zones where the bedrock was not encountered within 15 ft below the GSE, the drilled shafts' side resistance was calculated using the alpha (α) method for cohesive soils and beta (β) method for cohesionless soils. LRFD Resistance Factors of 0.55 for side resistance and 0.5 for tip resistance for cohesionless soils, and resistance factors of 0.45 for side resistance and 0.4 for tip resistance for cohesive soils are incorporated into the allowable capacities, respectively.

For the zones where the bedrock was encountered, the provided capacities are based on empirical values of weathered limestone strength properties and utilizing the IDOT Drilled Shaft Axial Capacity in Rock spreadsheet as provided by IDOT BBS Foundations and Geotechnical Unit. LRFD Resistance Factors of 0.55 for side resistance and 0.5 for tip resistance are incorporated into the allowable capacities, respectively. (See Exhibit F – Foundation Analysis)

Table 4.1.1 shows the summary of the boring selected by stationing. The estimated Drilled Shaft Axial Capacity summary of Factored Shaft Resistances available for various shaft diameters based on socket depths are shown in Tables 4.1.2 through 4.1.5 below.

Table 4.1.1 - Summary of Foundation Recommendations

Stationing	Boring	Bottom of NWA Elevation	Top of Rock
69+11.44 – 74+00.00	B-1	861.30	-
74+00.00 – 78+00.00	B-5	839.30	-
78+00.00 – 80+00.00	B-6	836.07	824.60
80+00.00 – 87+20.67	B-7	830.19	825.10

Table 4.1.2 - Estimated Drilled Shaft Axial Capacity for STA 69+11.44 – 74+00.00 (Boring B-1)

Diameter Socket (in.)	Socket Depth (ft.)	Nominal Shaft Resistance Available (kips) TIP	Factored Shaft Resistance Available (kips) TIP	Nominal Shaft Resistance Available (kips) SIDE	Factored Shaft Resistance Available (kips) SIDE
30	5	63.82	25.53	0.96	0.43
	10	141.37	70.69	16.06	8.74
	15	141.37	70.69	34.47	18.86
36	5	91.90	36.76	1.15	0.52
	10	203.58	101.79	19.27	10.48
	15	203.58	101.79	41.37	22.64
42	5	125.08	50.03	1.34	0.60
	10	277.09	138.54	22.48	12.23
	15	277.09	138.54	48.26	26.41
48	5	163.37	65.35	1.53	0.69
	10	361.91	180.96	25.70	13.98
	15	361.91	180.96	55.16	30.18

**Table 4.1.3 - Estimated Drilled Shaft Axial Capacity for STA 74+00.00 – 78+00.00
(Boring B-5)**

Diameter Socket (in.)	Socket Depth (ft.)	Nominal Shaft Resistance Available (kips) TIP	Factored Shaft Resistance Available (kips) TIP	Nominal Shaft Resistance Available (kips) SIDE	Factored Shaft Resistance Available (kips) SIDE
30	5	188.50	94.25	28.84	14.21
	10	64.80	32.40	65.83	34.56
	15	12.76	5.11	88.49	45.92
36	5	271.43	135.72	34.61	17.05
	10	93.31	46.65	78.99	41.47
	15	18.38	7.35	106.19	55.11
42	5	369.45	184.73	40.37	19.90
	10	127.00	63.50	92.16	48.38
	15	25.01	10.01	123.89	64.29
48	5	482.55	241.27	46.14	22.74
	10	165.88	82.94	105.33	55.29
	15	32.67	13.07	141.59	73.48

**Table 4.1.4 - Estimated Drilled Shaft Axial Capacity for STA 78+00.00 – 80+00.00
(Boring B-6)**

Diameter Socket (in.)	Socket Depth (ft.)	Nominal Shaft Resistance Available (kips) TIP	Factored Shaft Resistance Available (kips) TIP	Nominal Shaft Resistance Available (kips) SIDE	Factored Shaft Resistance Available (kips) SIDE
30	3	93	46	67	37
	5	104	52	111	61
	7	114	57	156	86
36	3	134	67	80	44
	5	150	75	134	74
	7	160	82	187	103
42	3	182	91	94	82
	5	204	102	156	86
	7	223	111	219	120

Diameter Socket (in.)	Socket Depth (ft.)	Nominal Shaft Resistance Available (kips) TIP	Factored Shaft Resistance Available (kips) TIP	Nominal Shaft Resistance Available (kips) SIDE	Factored Shaft Resistance Available (kips) SIDE
48	3	238	119	107	59
	5	266	133	178	98
	7	291	145	250	137

**Table 4.1.5 - Estimated Drilled Shaft Axial Capacity for STA 80+00.00 – 87+20.67
(Boring B-7)**

Diameter Socket (in.)	Socket Depth (ft.)	Nominal Shaft Resistance Available (kips) TIP	Factored Shaft Resistance Available (kips) TIP	Nominal Shaft Resistance Available (kips) SIDE	Factored Shaft Resistance Available (kips) SIDE
30	3	118	59	67	37
	5	127	63	111	61
	7	135	67	156	86
36	3	170	85	80	44
	5	182	91	134	74
	7	194	97	187	103
42	3	232	116	94	52
	5	248	124	156	86
	7	264	132	219	120
48	3	303	151	107	59
	5	324	162	178	98
	7	344	172	250	137

4.2 Lateral Pile Response

Generally, the geotechnical engineer provides soil parameters to the structural engineer so that an L-Pile program, or other approved software, can be used for the lateral or displacement analysis of the foundations. Table 4.2.1 and Table 4.2.2 are included for the structural engineer's use in determining lateral pile response.

Table 4.2.1 - Soil Parameters for Lateral Pile Load Analysis

Boring	Soil Description	Depth at Bot. of Layer (Ft.)	γ (pcf)	Short Term		Long Term		N Value (Ave.)	Assumed% Fines < #200	K (pci)	ϵ_{50}
				c (psf)	Φ (deg.)	c (psf)	Φ (deg.)				
B-1	Silty Clay Loam	861.14	120	1525	28	100	28	9	65	500	0.007
	Sandy Loam	853.64	120	-	33	-	33	18	35	90	-
	Clay Loam	851.14	120	2300	0	100	26	17	65	1000	0.005
B-2	Loam	864.57	120	-	32	-	32	20	25	90	-
	Gravel	859.57	125	-	31	-	38	16	3	-	-
	Sandy clay loam	845.57	120	-	33	-	33	19	45	90	-
B-3	Silty Clay Loam	855.37	120	1100	28	100	28	17	65	500	0.007
	Gravel	847.87	125	-	31	-	38	13	3	-	-
	Sandy clay loam	841.37	120	-	32	-	32	17	45	90	-
B-4	Silty Clay Loam	849.67	120	1500	28	100	28	18	65	500	0.007
	Gravel	844.67	125	-	32	-	38	21	3	-	-
	Sandy clay loam	840.67	120	-	33	-	33	20	45	90	-
	Clay Loam	838.17	120	-	0	150	26	22	65	2000	0.004
	Sandy Loam	835.67	120	-	34	-	34	23	35	90	-
	Silty Sand	833.17	115	-	30	-	30	9	25	25	-
	Silty Clay Loam	830.67	120	2100	28	100	28	14	65	1000	0.005
B-5	Silty Clay Loam	837.30	120	2100	28	100	28	17	65	1000	0.005
	Sandy clay loam	832.80	120	-	33	-	33	24	45	90	-
	Fine Sand	830.30	115	-	30	-	30	11	5	90	-
	Sandy Loam	827.80	120	-	29	-	29	8	35	25	-
	Silty Clay Loam	825.30	120	400	28	100	28	7	65	30	0.02
B-6	Silty Clay Loam	834.60	120	800	28	100	28	11	65	100	0.01
	Fine Sand	833.10	115	-	30	-	30	11	5	90	-
	Silty Loam	828.10	120	-	30	-	30	11	65	90	-
	Sandy Loam	824.60	120	-	30	-	30	12	35	90	-
B-7	Silty Clay Loam	827.55	120	800	28	100	28	9	65	100	0.01
	Sandy clay loam	826.05	120	-	29	-	29	9	45	25	-
B-8	Sandy Loam	816.09	120	-	39	-	39	51	35	225	-
B-9	Silty Loam	814.54	120	-	29	-	29	8	65	25	-
	Sandy Loam	810.54	120	-	36	-	36	35	35	225	-

Table 4.2.2 - Rock Parameters for Lateral Pile Load Analysis

Rock Type	γ (psf)	Q_u (tsf)	Φ (deg.)
Limestone	145	25	45

5.0 CONSTRUCTION CONSIDERATIONS

5.1 Construction Activities

Construction activities should be performed in accordance with the current IDOT Standard Specifications for Road and Bridge Construction and any pertinent Special Provisions or Policies.

Should any design considerations assumed by KEG change, KEG should be contacted to determine if the recommendations stated in this report still apply.

5.2 Temporary Sheet piling and Soil Retention

Temporary shoring is not anticipated as the wall will be constructed on ground level.

5.3 Site and Soil Conditions

Provisions of the Standard Specifications should adequately address site and soil conditions.

6.0 COMPUTATIONS

Computations and analyses for specific circumstances, if any, are included as exhibits. Please refer to each section of the report for reference to the exhibit containing any such calculations or analysis used.


7.0 GEOTECHNICAL DATA

Soil boring logs and subsurface profiles can be found in Exhibit D and Exhibit E. Foundation Design Tables can be found in Exhibit F.

8.0 LIMITATIONS

The recommendations provided herein are for the exclusive use of Alfred Benesch & Company and the Illinois Department of Transportation (IDOT) District 2. They are specific only to the project described. They are based on the subsurface information obtained by IDOT at nine boring locations within the structure area, KEG's understanding of the project as described herein, and geotechnical engineering practice consistent with the standard of care. No other warranty is expressed or implied. KEG should be contacted if conditions encountered during construction are not consistent with those described.

EXHIBIT A
LOCATION MAP



Proposed Noise Wall 20

Proposed Noise Wall 20



LOCATION MAP

I-39 Noise
Abatement Wall 20
Winnebago County,
Illinois

Exhibit No.

A

KEG JOB #19-1138.00

EXHIBIT B
BORING PLAN



BORING LOCATION MAP

I-39 Noise
Abatement Wall 20
Winnebago County,
Illinois

Exhibit No.

B

KEG JOB #19-1138.00

EXHIBIT C

GENERAL PLAN AND ELEVATION PLAN (GP&E)

MODEL: Default
FILE NAME: pw:\bnesch-pw-01\Documents\10800s\10800s\10800.00\Eng_Docs\CAD_Sheets\do you mean\101W7009-64C24-001-GPE1.dgn

Range 2 E, 3rd P.M.

Pr. Noise Wall

Twp. 43 N

LINDNER RD

MULFORD RD

PERRYVILLE RD

N

LOCATION SKETCH




GENERAL PLAN AND ELEVATION
NOISE ABATEMENT WALL
F.A.I ROUTE 39 SEC. (201-3)R & (4-1,5)R
WINNEBAGO COUNTY
STA. 69+11.46 TO STA. 87+20.69
STRUCTURE NO. 101-N7009




STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET 1 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1.5)R	WINNEBAGO	1552	787
		CONTRACT NO. 64C24		
ILLINOIS		FED. AID PROJECT		



ELEVATION



PLAN

Notes:

Offsets are measured from $\mathbb{B}$ Ramp AD to $\mathbb{C}$ Noise Abatement Wall or Boring location.

See Data Table on sheet 3 of 9 for Offsets and Theoretical Elevations along the $\mathbb{C}$ of Noise Abatement Wall.

Theoretical Top of NAW Elev., Theoretical Bottom of NAW Elev., Existing Grade Elev. at $\mathbb{C}$ of NAW, and Finished Grade Elev. at $\mathbb{C}$ of NAW shall be taken as straight lines in the segments between each pair of stations shown in the Data Table on sheet 3 of 9.

Access doors are to be spaced at 300' maximum intervals.

LEGEND

$\mathbb{B}$	Noise Abatement Wall Soil Boring
---	Existing Fence
---	Access Control
---	Frontier Underground Telephone
---	Underground Electric

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

NOISE ABATEMENT WALL GENERAL PLAN AND ELEVATION II
STRUCTURE NO. 101-N7009

SHEET 2 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1.5)R	WINNEBAGO	1552	788
CONTRACT NO. 64C24				
ILLINOIS FED. AID PROJECT				



QUIGG ENGINEERING INC

USER NAME =	zdauidson	DESIGNED -	ZLD	REVISED -	
101W7009-64C24-002-GPE2.dgn		CHECKED -	KWB	REVISED -	
PLOT SCALE =		DRAWN -	ZLD	REVISED -	
PLOT DATE =	05/09/2024	CHECKED -	MDC	REVISED -	


1. *All excavation and grading below the finished grade elevation required for installation of the Noise Abatement Wall elements shall be included in the cost of Noise Abatement Wall, Ground Mounted.*
2. *Contractor shall follow requirements of Guide Bridge Special Provision "Noise Abatement Wall, Ground Mounted" for material, design, fabrication, construction and erection requirements of the proposed Noise Abatement Wall.*
3. *The Contractor shall field verify location of the existing utilities prior to construction. The Contractor shall take precautions not to damage existing utilities. Any such damage shall be repaired by the Contractor at no additional cost. All adjacent utilities shall be shown on the shop drawings.*
4. *Noise Abatement Wall drilled shaft foundation diameter, depth and spacing to be determined by the Contractor.*
5. *Precast panels for the Ground Mounted Noise Abatement Walls shall be cast using form liners with a simulated limestone surface. Form liners shall be used on both faces of the panels. The form liner shall match the exact size of each panel such that there are no joints crossing the stone modules. The relief shall be an average of 1½" deep and no greater than 2½" deep at any point. The desired appearance is as follows:*




6. *Form liners shall be made from high-strength elastomeric urethane and be removable without causing concrete surface damage or weakness in the substrate. Form release agents shall be non-staining, non-residual, non-reactive, and shall not contribute to the degradation of the form liner material.*
7. *The following form liner manufacturers have been pre-approved to provide the listed pattern for the simulated limestone surface:*
 - a. *Custom Rock International, St. Paul, MN (Jim Rogers; 800-637-2447)
#1104-R2 14¾" Random Cut Stone or #11016 16" Random Cut Stone*
 - b. *Milestones Incorporated, Hudson, WI (Paul Nasvik; 715-381-9660)
#MS-1018 16" Weathered Limestone*
 - c. *Architectural Polymers, New Ringgold, PA (Rick Fasching; 610-824-3322)
#893 14" Quarry Stone or #894 16" Quarry Stone*

Other products will be considered, provided sufficient information is submitted 30-days prior to use to allow the Engineer to determine that products proposed are equivalent to those named.

8. *Form liners shall be used in accordance with the manufacturer's recommendations, including, but not limited to, installation and removal methods, form release agents, cleaning procedures, inspection procedures, repair procedures, curing methods, concrete slump requirements, and consolidation methods to achieve the highest quality concrete appearance possible. Manufacturer recommendations shall not supplant requirements listed elsewhere in the Contract Documents without prior approval from the Engineer.*
9. *The finished exposed formed concrete surfaces shall be free of visible vertical seams, horizontal seams, and butt joint marks after removing the form liners. Grinding and chipping of finished formed surfaces shall be avoided.*
10. *The Contractor shall provide a full-size precast panel mockup containing the form liner surface. Upon receipt of comments from inspection of the mockup, adjustments or corrections shall be made where imperfections are found. If required, additional mockups shall be prepared when the initial mockup is found to be unsatisfactory.*
11. *All work and materials associated with form liners and mockups, including adjustments or corrections needed to address mockup comments and additional mockups, if required, will not be paid for separately but shall be included in the cost of Noise Abatement Wall, Ground Mounted.*



NAME PLATE LOCATION

PROFILE GRADE

(Along $\underline{B}$ Ramp AD)

2020 AASHTO LRFD Bridge Design Specifications, 9th Edition

Strength III or V Wind: 35 psf
Service I Wind: 15 psf

FIELD UNITS

f'c = 4,000 psi
fy = 60,000 psi (Reinforcement)
fy = 50,000 psi (Struct. Steel, M270 Grade 50, posts)
fy = 36,000 psi (Struct. Steel, M270 Grade 36, all
other structural steel)

PRECAST UNITS

$f'_c = 4,500 \text{ psi}$
 $f_y = 60,000 \text{ psi (Reinforcement)}$
 $f_y = 65,000 \text{ psi (Welded Wire Reinforcement)}$


TOTAL BILL OF MATERIAL

ITEM	UNIT	TOTAL
Name Plates	Each	1
Noise Abatement Wall, Ground Mounted	Sq. Ft.	37,435

NOISE REDUCTION DATA TABLE

Noise Wall Structure Number	Face	From Sta.	To Sta.	Noise Reduction Coefficient	Comments
101-N7009	Ramp AD Face	69+11.46	87+20.69	Reflective	-
	Residential Face	69+11.46	87+20.69	Reflective	-

 QUIGG ENGINEERING INC	USER NAME = zdavkdson	DESIGNED - ZLD	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	NOISE ABATEMENT WALL GENERAL DETAILS STRUCTURE NO. 101-N7009	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	101W7009-64C24-003-General Details.dgn	CHECKED - KWB	REVISED -			39	(201-3)R & (4-1,5)R	WINNEBAGO	1552	789
	PLOT SCALE =	DRAWN - ZLD	REVISED -			CONTRACT NO. 64C24				
	PLOT DATE = 05/09/2024	CHECKED - MDC	REVISED -			SHEET 3 OF 9 SHEETS				





SOIL BORING LOG

Page 1 of 1

Date 5/22/23

ROUTE FAI 39 DESCRIPTION P92-111-08 - Noise Wall from Linden Road S, 0.35 mi. LOGGED BY W. Garza

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO.	D	B	U	M	Surface Water Elev.	ft	D	B	U	M
Station	E	L	C	O	Stream Bed Elev.	ft	E	L	C	O
BORING NO.	P	O	S	I	Groundwater Elev.:		P	O	S	I
Station	T	W	Qu	T	First Encounter	ft	H	S	Qu	T
Offset	H	S			Upon Completion	ft				
Ground Surface Elev.	(ft)	(/6")	(tsf)	(%)	After	ft	(ft)	(/6")	(tsf)	(%)
MEDIUM brown SILTY CLAY LOAM			0.8	18	STIFF light brown CLAY LOAM TILL (continued)	848.6	7	1.9	18	
			P		End of Boring					
867.6		2								
VERY STIFF light brown SITLY CLAY LOAM		3	2.3	15						
		7	B							
865.1										
STIFF light brown CLAY LOAM		3								
		3	1.3	16						
		5	P							
862.6										
STIFF light brown CLAY LOAM with SAND		2								
		5	1.7	19						
		6	B							
860.1										
STIFF light brown SANDY LOAM with GRAVEL		2								
		10	1.7	16						
		9	B							
857.6										
STIFF light brown SANDY LOAM		3								
		10	1.4	16						
		12	B							
855.1										
STIFF light brown SANDY CLAY LOAM with DRY SANDY GRAVEL LENS		4								
		8	1.2	16						
		7	B							
852.6										
VERY STIFF gray CLAY LOAM		3								
		6	2.7	18						
		10	B							
850.1										
		4								

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 5/22/23

ROUTE FAI 39 DESCRIPTION P92-111-08 - Noise Wall from Linden Road S, 0.35 mi. LOGGED BY W. Garza

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO.	D	B	U	M	Surface Water Elev.	ft	D	B	U	M
Station	E	L	C	O	Stream Bed Elev.	ft	E	L	C	O
BORING NO.	P	O	S	I	Groundwater Elev.:		P	O	S	I
Station	T	W	Qu	T	First Encounter	ft	H	S	Qu	T
Offset	H	S			Upon Completion	ft				
Ground Surface Elev.	(ft)	(/6")	(tsf)	(%)	After	ft	(ft)	(/6")	(tsf)	(%)
MEDIUM brown LOAM			0.8	15	VERY STIFF gray SANDY CLAY LOAM with FINE SAND LENS (continued)	845.6	10	2.3	11	
			P		End of Boring					
864.6										
MEDIUM tan WEATHERED LIMESTONE		15								
		11								
		9								
862.1										
MEDIUM tan WEATHERED LIMESTONE FILL		8								
		7		6						
859.6										
STIFF light brown SANDY CLAY LOAM TILL		6								
		5	1.3	12						
		6	B							
857.1										
VERY STIFF light brown SANDY CLAY LOAM		6								
		9	2.7	15						
		14	B							
854.6										
VERY STIFF light brown SANDY CLAY LOAM		5								
		7	3.9	13						
		10	B							
852.1										
VERY STIFF light brown SANDY CLAY LOAM		5								
		8	2.9	14						
		13	B							
849.6										
STIFF brown SANDY CLAY LOAM		5								
		7	1.2	17						
		10	B							
847.1										
		5								

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)

MODEL: Default
FILE NAME: pw:\benesch-pw.bentley.com\benesch-pw-01\Documents\10800s\10800s\CAD_Sheets\do you mean\101W7009-64C24-005-Boring_Logs.dgn



QUIGG ENGINEERING INC

USER NAME =	z davidson	DESIGNED -	ZLD	REVISED -	
101W7009-64C24-005-Boring_Logs.dgn	CHECKED -	KWB	REVISED -		
PLOT SCALE =		DRAWN -	ZLD	REVISED -	
PLOT DATE =	05/09/2024	CHECKED -	MDC	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BORING LOGS
STRUCTURE NO. 101-N7009

SHEET 5 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1.5)R	WINNEBAGO	1552	791
CONTRACT NO. 64C24				
ILLINOIS FED. AID PROJECT				

Page 1 of 1Date 5/23/23

ROUTE	FAI 39	DESCRIPTION	P92-111-08 - Noise Wall from Linden Road S, 0.35 mi.	LOGGED BY	W. Garza
-------	--------	-------------	--	-----------	----------

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnabago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

[illegible]

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



Page 1 of 1

Date 5/23/23

ROUTE	FAI 39	DESCRIPTION	P92-111-08 - Noise Wall from Linden Road S, 0.35 mi.	LOGGED BY	W. Garza
-------	--------	-------------	--	-----------	----------

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnabago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO. _____ Station _____	DEPTH (ft)	BLOW COUNT (/6")	UCS Qu (tsf)	MOISTURE CONTENT (%)	Surface Water Elev. _____ ft Stream Bed Elev. _____ ft Groundwater Elev.: First Encounter _____ ft Upon Completion _____ ft After _____ Hrs. _____ ft	DEPTH (ft)	BLOW COUNT (/6")	UCS Qu (tsf)	MOISTURE CONTENT (%)
BORING NO. <u>B-4</u> Station <u>75+00</u> Offset <u>28.0 ft RT</u> Ground Surface Elev. <u>851.67</u> ft									
STIFF brown SILTY CLAY LOAM			1.5	11	VERY STIFF dark gray SILT CLAY LOAM (continued) 830.7	5	9	2.1	21
849.7			P		End of Boring				
MEDIUM tan DRY WEATHERED LIMESTONE FILL		13							
		11							
		7							
847.2									
MEDIUM tan DRY WEATHERED LIMESTONE FILL		3							
		12							
		13							
Hard drilling									
844.7									
VERY STIFF brown SANDY CLAY LOAM		2							
		5	2.9	14					
		9	S						
842.2									
STIFF brown SANDY CLAY LOAM TILL		5							
		7	1.3	13					
		19	B						
839.7									
VERY STIFF light brown CLAY LOAM		9							
		10	2.9	20					
		12	B						
837.2									
MEDIUM brown SANDY LOAM with FINE SAND LENS		9							
		12	1.0	10					
		11	S						
834.7									
STIFF tan SILTY SAND with FINE SAND LENS		4							
		3	1.1	16					
		6	S						
832.2									
		3							

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



USER NAME =	zdauidson	DESIGNED -	ZLD	REVISED -	
101W7009-64C24-006-Boring Logs.dgn		CHECKED -	KWB	REVISED -	
PLOT SCALE =		DRAWN -	ZLD	REVISED -	
PLOT DATE =	05/09/2024	CHECKED -	MDC	REVISED -	

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

BORING LOGS
STRUCTURE NO. 101-N7009

SHEET 6 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1.5)R	WINNEBAGO	1552	792
		CONTRACT NO. 64C24		
ILLINOIS		FED. AID PROJECT		

MODEL: Default
FILE NAME: pw:\ibenesch-pw.bentley.com\benesch-pw-01\Documents\10800s\10800s\10800.00\Eng_Docs\CAD_Sheets\do you mean\101W77009-6\CD24-006-Boring_Logs.dgn

Page 1 of 1Date 5/24/23

ROUTE	FAI 39	DESCRIPTION	P92-111-08 - Noise Wall from Linden Road S, 0.35 mi.	LOGGED BY	W. Garza
-------	--------	-------------	--	-----------	----------

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnabago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

[illegible]

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)

Page 1 of 1

Date 5/25/23

P92-111-08 - Noise Wall from Linden Road S, 0.35				
ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY
				W. Garza

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnabago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO. _____ Station _____	D E P T H	B L O W S	U C S Qu	M O I S T	Surface Water Elev. _____ ft Stream Bed Elev. _____ ft
BORING NO. B-6 Station 79+00 Offset 35.0 ft RT Ground Surface Elev. 836.60 ft	(ft)	(/6")	(tsf)	(%)	Groundwater Elev.: First Encounter _____ ft Upon Completion _____ ft After _____ Hrs. _____ ft
MEDIUM brown SILTY CLAY LOAM	834.6	3	0.8 P	11	
MEDIUM brown MOIST FINE SAND	832.1	5 6		17	
SOFT tan SILTY LOAM	829.6	2 3 3	0.3 P	24	
VERY SOFT light brown SILTY LOAM with SAND LENS	827.1	5 8 8	0.2 P	19	
MEDIUM tan SANDY LOAM	824.6	4 5 7	0.6 P	17	
VERY DENSE tan WEATHERED LIMESTONE	822.1	28 100/3			
End of Boring	-15				
	-20				

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



QUIGG ENGINEERING INC

5/9/2024 3:38:07 PM

USER NAME	=	zdavidson
101W7009-64C24-007-Boring Logs.dgn		
PLOT SCALE	=	
PLOT DATE	=	05/09/2024

DESIGNED - ZLD	REVISED -
CHECKED - KWB	REVISED -
DRAWN - ZLD	REVISED -
CHECKED - MDC	REVISED -

REVISED	-
REVISED	-
REVISED	-
REVISED	-

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

BORING LOGS
STRUCTURE NO. 101-N7009

SHEET 7 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1,5)R	WINNEBAGO	1552	793
		CONTRACT NO. 64C24		
ILLINOIS		FED. AID PROJECT		

ILLINOIS	FED. AID PROJECT
----------	------------------

Page 1 of 1

Date 5/30/23

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

STRUCT. NO. _____	D	B	U	M	Surface Water Elev. _____	ft
Station _____	E	L	C	O	Stream Bed Elev. _____	ft
	P	O	S	I		
BORING NO. _____ B-7	T	W	S	S	Groundwater Elev.: _____	
Station _____ 81+00	H	S	Qu	T	First Encounter _____	ft
Offset _____ 35.0 ft RT					Upon Completion _____	ft
Ground Surface Elev. _____ 829.55	ft	(ft)	(/6")	(tsf)	After _____ Hrs. _____	ft

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Illinois Department
of Transportation
Division of Highways

Page 1 of 1

Date 5/30/23

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

STRUCT. NO. _____	D	B	U	M	Surface Water Elev. _____	ft
Station _____	E	L	C	O	Stream Bed Elev. _____	ft
	P	O	S	I		
BORING NO. _____ B-9	T	W		S	Groundwater Elev.: _____	
Station _____ 83+00	H	S	Qu	T	First Encounter _____	ft
Offset _____ 40.0 ft RT					Upon Completion _____	ft
Ground Surface Elev. _____ 820.59	ft	(ft)	(6")	(tsf)	(%)	After _____ Hrs. _____
						ft

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

SHEET 8 OF 9 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1.5)R	WINNEBAGO	1552	794
		CONTRACT NO. 64C24		
ILLINOIS		FED. AID PROJECT		



Page 1 of 1

Date 5/30/23

SECTION (201-3)K LOCATION Cherry Valley, NE 1/4 9

COUNTY Winnabago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
39	(201-3)R & (4-1,5)R	WINNEBAGO	1552	795
		CONTRACT NO. 64C24		
ILLINOIS		FED. AID PROJECT		

EXHIBIT D
BORING LOGS

Page 1 of 1

Date 5/22/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

STRUCT. NO. _____ Station _____		DEPTH (ft)	BLOW S (/6")	UCS Qu (tsf)	MOIST (%)	Surface Water Elev. _____ ft Stream Bed Elev. _____ ft		DEPTH (ft)	BLOW S (/6")	UCS Qu (tsf)	MOIST (%)
BORING NO. _____ B-1 Station _____ 69+50 Offset _____ 22.0 ft RT Ground Surface Elev. _____ 869.64 ft						Groundwater Elev.: First Encounter _____ ft Upon Completion _____ ft After _____ Hrs. _____ ft					
MEDIUM brown SILTY CLAY LOAM				0.8 P	18	STIFF light brown CLAY LOAM TILL (continued) 848.6		7 11		1.9 B	18
867.6			2			End of Boring					
VERY STFF light brown SITLY CLAY LOAM			3 7	2.3 B	15						
865.1			3								
STIFF light brown CLAY LOAM			3 5	1.3 P	16						
862.6			2								
STIFF light brown CLAY LOAM with SAND			5 6	1.7 B	19						
860.1			2								
STIFF light brown SANDY LOAM with GRAVEL			10 9	1.7 B	16						
857.6			3								
STIFF light brown SANDY LOAM			10 12	1.4 B	16						
855.1			4								
STIFF light brown SANDY CLAY LOAM with DRY SANDY GRAVEL LENS			8 7	1.2 B	16						
852.6			3								
VERY STIFF gray CLAY LOAM			6 10	2.7 B	18						
850.1			4								

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/22/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

STRUCT. NO. _____ Station _____		D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev. _____ ft Stream Bed Elev. _____ ft		D E P T H (ft)	B L O W S (/6")	U C S Qu (tsf)	M O I S T (%)
BORING NO. _____ B-2 Station _____ 71+00 Offset _____ 23.0 ft RT Ground Surface Elev. _____ 866.57 ft						Groundwater Elev.: First Encounter _____ ft Upon Completion _____ ft After _____ Hrs. _____ ft					
MEDIUM brown LOAM				0.8 P	15	VERY STIFF gray SANDY CLAY LOAM with FINE SAND LENS (continued)		10 16	2.3 S	11	
864.6						End of Boring					
MEDIUM tan WEATHERED LIMESTONE			15								
			11								
			9								
862.1											
MEDIUM tan WEATHERED LIMESTONE FILL			6		6						
			7								
859.6											
STIFF light brown SANDY CLAY LOAM TILL			6	1.3 B	12						
			5								
			6								
857.1											
VERY STIFF light brown SANDY CLAY LOAM			6	2.7 B	15						
			9								
			14								
854.6											
VERY STIFF light brown SANDY CLAY LOAM			5	3.9 B	13						
			7								
			10								
852.1											
VERY STIFF light brown SANDY CLAY LOAM			5	2.9 B	14						
			8								
			13								
849.6											
STIFF brown SANDY CLAY LOAM			5	1.2 B	17						
			7								
			10								
847.1											
			5								

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/23/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/23/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

STRUCT. NO. _____ Station _____	D E P T H	B L O W S	U C S Qu	M O I S T (%)	Surface Water Elev. _____ ft Stream Bed Elev. _____ ft	D E P T H (ft)	B L O W S (/6")	U C S (tsf)	M O I S T (%)
BORING NO. _____ B-4 Station _____ 75+00 Offset _____ 28.0 ft RT Ground Surface Elev. _____ 851.67 ft	(ft)	(/6")	(tsf)	(%)	Groundwater Elev.: First Encounter _____ ft Upon Completion _____ ft After _____ Hrs. _____ ft	(ft)	(/6")	(tsf)	(%)
STIFF brown SILTY CLAY LOAM			1.5 P	11	VERY STIFF dark gray SILT CLAY LOAM (continued) 830.7	5 9	2.1 B	21	
849.7					End of Boring				
MEDIUM tan DRY WEATHERED LIMESTONE FILL		13 11 7							
847.2									
MEDIUM tan DRY WEATHERED LIMESTONE FILL		3 12 13							
Hard drilling									
844.7									
VERY STIFF brown SANDY CLAY LOAM		2 5 9	2.9 S	14					
842.2									
STIFF brown SANDY CLAY LOAM TILL		5 7 19	1.3 B	13					
839.7									
VERY STIFF light brown CLAY LOAM		9 10 12	2.9 B	20					
837.2									
MEDIUM brown SANDY LOAM with FINE SAND LENS		9 12 11	1.0 S	10					
834.7									
STIFF tan SILTY SAND with FINE SAND LENS		4 3 6	1.1 S	16					
832.2									
20		3							

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1Date 5/24/23

P92-111-06 - Noise Wall from Linden Road S, 0.35
mi.

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/25/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/30/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/30/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------

SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

Page 1 of 1

Date 5/30/23

ROUTE	FAI 39	DESCRIPTION	mi.	LOGGED BY	W. Garza
-------	--------	-------------	-----	-----------	----------



SECTION (201-3)K **LOCATION** Cherry Valley, NE 1/4 9

COUNTY Winnabago **DRILLING METHOD** Hollow Stem Auger **HAMMER TYPE** CME-45 Automatic

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

EXHIBIT E
SUBSURFACE PROFILE

PRINTERMOD2 11x17 19-1138.00 NOISE WALL 20.GPJ IL_DOT.GDT 3/8/24




**Illinois Department
of Transportation**
Division of Highways

NOT TO HORIZONTAL SCALE

SUBSURFACE PROFILE

Route: FAI 39
Section: (201-3)K
County: Winnabago

PRINTERMOD2 11x17 19-1138.00 NOISE WALL 20.GPJ IL_DOT.GDT 3/8/24



NOT TO HORIZONTAL SCALE

SUBSURFACE PROFILE

Route: FAI 39
Section: (201-3)K
County: Winnabago

EXHIBIT F
FOUNDATION ANALYSIS

Kaskaskia Engineering Group, LLC

GWT:	-
elev. Top of Drilled Shaft (ft):	861.3
Diameter(in)	48.00
At(ft²)	12.57

[illegible]

Drilled Shafts Side and Toe Resistance

Kaskaskia Engineering Group, LLC

Project: NAW-20 (N7009)
Project Number: 19-1138.00

Substructure: Noise Wall
Boring Number: B-5

GWT -
elev. Top of Drilled Shaft (ft): 839.3
Diameter(in) 30.00
At(ft²) 4.91

Soil Parameters								Side Friction						Tip Resistance		Qt (kips)	Factored Qt (kips)	Cumulative Qs (kips)	Cumulative Factored Qs (kips)
Layer	Description	Thickness (ft)	z(ft)	γ(pcf)	Su (psf)	N	N60	σ'(psf)	α	β	As(ft²)	fs (ksf)	Nc*	q't (ksf)					
1	Silty Clay Loam	2.00	2.00	120.00	2100.0			120	0.50		15.71	1.05	9	18.9	92.78	37.11	16.49	7.42	
2	Sandy Clay Loam	3.00	5.00	120.00		24.0	32	420		1.25	23.56	0.52		38.4	188.50	94.25	28.84	14.21	
3	Sandy Clay Loam	1.50	6.50	120.00		24.0	32	690		1.18	11.78	0.81		38.4	188.50	94.25	38.40	19.47	
4	Fine Sand	2.50	9.00	115.00		11.0	15	924		1.12	19.63	1.04		18	88.36	44.18	58.79	30.69	
5	Sandy loam	1.00	10.00	120.00		8.0	11	1128		0.79	7.85	0.90		13.2	64.80	32.40	65.83	34.56	
6	sandy loam	1.50	11.50	120.00		8.0	11	1278		0.78	11.78	0.99		13.2	64.80	32.40	77.50	40.97	
7	silty clay loam	3.50	15.00	120.00	400.0			1578	1.00		27.49	0.40	6.5	2.6	12.76	5.11	88.49	45.92	
8																			
9																			
10																			
11																			
12																			
13																			
14																			
15																			



DRILLED SHAFT AXIAL CAPACITY IN ROCK -
DOLOMITE, LIMESTONE, SANDSTONE, AND HARD SHALE

Drilled Shaft Dia.'s for Design Table

STRUCTURE ===== NW 20
SUBSTRUCTURE & REFERENCE BORING ===== B-6
GROUND SURFACE ELEVATION ===== 836.60 FT
GROUND WATER ELEVATION ===== FT
ESTIMATED TOP OF ROCK ELEVATION ===== 824.60 FT
DRILLED SHAFT DIAMETER IN ROCK ===== 48 IN.
FACTORED AXIAL LOAD ===== KIPS
DRILLED SHAFT CONCRETE STRENGTH, f_c ===== 4.0 KSI

FOUNDATION REDUNDANCY === REDUNDANT

30 IN.
36 IN.
42 IN.
48 IN.
IN.
IN.

SOCKET DEPTH (FT)	TIP ELEV. (FT)	LAYER THICK. (FT)	UNCONFINED COMPRESSIVE STRENGTH (q _u) (KSF)	ROCK TYPE	GSI	ROCK CONDITION	RQD (%)	JOINT TYPE	ROCK INTACT OR TIGHTLY JOINTED?	SIDE RESISTANCE						AVG. q _u W/IN 2 - SHAFT DIA. (KSF)	TIP RESISTANCE			COMBINED SIDE & TIP RESISTANCE					
										NOM. RESIST. (KIPS)	Σ NOM. RESIST. (KIPS)	Σ FACT. RESIST. (KIPS)	SETTLEMENT				NOM. RESIST. (KIPS)	FACT. RESIST. (KIPS)	SETTL. w _{Rn} (IN.)	R _p /R _n	NOM. RESIST. (KIPS)	FACT. RESIST. (KIPS)	SETTLEMENT		
													Q _{C1} (KIPS)	w _{C1} (IN.)	w _{Rn} (IN.)								Q _{C1} (KIPS)	w _{C1} (IN.)	w _{Rn} (IN.)
3.00	821.60	3.00	25.0	Limestone	40	Fractured	50	Closed	No	107	107	59	41	0.006	0.758	25.0	303	151	0.093	0.86	352	178	65	0.006	0.071
5.00	819.60	2.00	25.0	Limestone	40	Fractured	50	Closed	No	71	178	98	69	0.008	0.764	25.0	324	162	0.065	0.79	408	208	103	0.008	0.078
7.00	817.60	2.00	25.0	Limestone	40	Fractured	50	Closed	No	71	250	137	97	0.010	0.767	25.0	344	172	0.071	0.74	466	239	138	0.010	0.085
17.00	807.60	10.00	25.0	Limestone	40	Fractured	50	Closed	No	357	607	334	237	0.016	0.776										



DRILLED SHAFT AXIAL CAPACITY IN ROCK -
DOLOMITE, LIMESTONE, SANDSTONE, AND HARD SHALE

Drilled Shaft Dia.'s for Design Table

STRUCTURE ===== NW 20
SUBSTRUCTURE & REFERENCE BORING ===== B-7
GROUND SURFACE ELEVATION ===== 829.55 FT
GROUND WATER ELEVATION ===== FT
ESTIMATED TOP OF ROCK ELEVATION ===== 825.10 FT
DRILLED SHAFT DIAMETER IN ROCK ===== 30 IN.
FACTORED AXIAL LOAD ===== KIPS
DRILLED SHAFT CONCRETE STRENGTH, f_c ===== 4.0 KSI

FOUNDATION REDUNDANCY === REDUNDANT

30 IN.
36 IN.
42 IN.
48 IN.
IN.
IN.

SOCKET DEPTH (FT)	TIP ELEV. (FT)	LAYER THICK. (FT)	UNCONFINED COMPRESSIVE STRENGTH (q _u) (KSF)	ROCK TYPE	GSI	ROCK CONDITION	RQD (%)	JOINT TYPE	ROCK INTACT OR TIGHTLY JOINTED?	SIDE RESISTANCE						AVG. q _u W/IN 2 - SHAFT DIA. (KSF)	TIP RESISTANCE			COMBINED SIDE & TIP RESISTANCE					
										NOM. RESIST. (KIPS)	Σ NOM. RESIST. (KIPS)	Σ FACT. RESIST. (KIPS)	SETTLEMENT				NOM. RESIST. (KIPS)	FACT. RESIST. (KIPS)	SETTL. w _{Rn} (IN.)	R _p /R _n	NOM. RESIST. (KIPS)	FACT. RESIST. (KIPS)	SETTLEMENT		
													Q _{C1} (KIPS)	w _{C1} (IN.)	w _{Rn} (IN.)								Q _{C1} (KIPS)	w _{C1} (IN.)	w _{Rn} (IN.)
3.00	822.10	3.00	25.0	Limestone	40	Fractured	50	Closed	No	67	67	37	26	0.005	0.477	25.0	93	46	0.035	0.75	124	64	39	0.005	0.036
5.00	820.10	2.00	25.0	Limestone	40	Fractured	50	Closed	No	45	111	61	43	0.007	0.480	25.0	104	52	0.033	0.65	160	83	60	0.007	0.043
7.00	818.10	2.00	25.0	Limestone	40	Fractured	50	Closed	No	45	156	86	61	0.008	0.482	25.0	114	57	0.045	0.57	198	103	80	0.008	0.051
17.00	808.10	10.00	25.0	Limestone	40	Fractured	50	Closed	No	223	379	208	149	0.014	0.490										