F.A.P. RTE.	SECTION		COUNT	Ý	TOTAL SHEETS	SHEET NO.
347	(LW&LY) F	RS-2	KAN	Ξ	18	2
STA. TO STA.						
FED. RO	AD DIST. NO. 7	ILLINOI	S FED.	AID	PROJECT	*
	271121771200000000000000000000000000000		CONT	RAC	T NO.: 6	2750

INDEX OF SHEETS

SHEET NO.	DESCRIPTION	
1	COVER SHEET	0000
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES	4422
3	SUMMARY OF QUANTITIES	6040
4	EXISTING AND PROPOSED TYPICAL SECTIONS	6060
5	ROADWAY AND PAVEMENT MARKING PLANS	7013
6-7	DETECTOR LOOP REPLACEMENT PLANS	7016
8	DETAILS FOR FRAMES AND LIDS ADJUSTMENTS WITH MILLING	7017
9	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	7020
10	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	
11	BUTT JOINT AND HMA TAPER DETAILS	
12	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS, AND DRIVEWAYS	
13	TYPICAL APPLICATION FOR RAISED REFLECTIVE PAVEMENT MARKERS	
14	DISTRICT ONE TYPICAL PAVEMENT MARKINGS	
15	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS	
16	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING	
17	ARTERIAL ROAD INFORMATION SIGN	
18	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURF.	ACING

STATE STANDARDS

000001-04	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
442201 -02	CLASS C AND D PATCHES
604091 -0 l	FRAME AND GRATES, TYPE 24
606001 -03	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701301 -02	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701606 -04	URBAN LANE CLOSURE MULTILANE 2W WITH MOUNTABLE MEDIAN
701701 -04	URBAN LANE CLOSURE, MULTILANE INTERSECTION
702001- 06	TRAFFIC CONTROL DEVICES

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION REQUIRED).

3 METER (10 FEET) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF GENEVA.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (11/2INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), - IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MR. DON CHIARUGI. AREA TRAFFIC FIELD ENGINEER AT (847) 741-9857 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE ARTERIAL TRAFFIC CONTROL AREA SUPERVISOR A MINIMUM OF 72 HOURS PRIOR TO BEGINNING WORK.

> ILLINOIS DEPARTMENT OF TRANSPORTATION ILL. ROUTE 38 (STATE STREET) FROM ILL. 25 TO EAST SIDE DRIVE (7th ST.)

> > INDEX OF SHEETS LIST OF STATE STANDARDS

SCALE: VERT.

DATE 5/24/2007

PLAN NOTES DRAWN RY