

TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEW

NOTES:

- A. FOR NO LANE RESTRICTION ON THE SIDE ROAD OR DRIVEWAYS
- 1. SIDE ROAD WITH A SPEED LIMIT OF 60 km/h (40 MPH) OR LESS AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
- d) ONE ROAD CONSTRUCTION AHEAD SIGN 900×900 (36×36) WITH A FLASHER AND FLAG MOUNTED ON IT APPROXIMATELY 60 m (200°) IN ADVANCE OF THE MAIN ROUTE.
- b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE I, TYPE II OR TYPE III BARRICADES, 1/3 OF THE CROSS SECTION OF THE CLOSED PORTION.
- 2. SIDE ROAD WITH A SPEED LIMIT GREATER THAN 60 km/h (40 MPH) AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
- c) ONE ROAD CONSTRUCTION AHEAD SIGN 1.2 m x 1.2 m (48x48) WITH A FLASHER MOUNTED ON IT APPROXIMATELY 150 m (500') IN ADVANCE OF THE MAIN ROUTE.
- b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE III BARRICADES, 1/2 OF THE CROSS SECTION OF THE CLOSED PORTION.
- 3. WHEN THE SIDE ROAD LIES BETWEEN THE BEGINNING OF THE MAINLINE SIGNING AND THE WORK ZONE, A SINGLE HEADED ARROW (M6-1) SHALL BE USED IN LIEU OF THE DOUBLE HEADED ARROW (M6-4).

- B. FOR A LANE CLOSURE ON A SIDE ROAD OR DRIVEWAY:
- USE APPLICABLE PORTIONS OF THE TYPICAL APPLICATION OF TR CONTROL DEVICES (STD. 701501, STD. 701606 OR THE APPROPRIA THE SPACING OF SIGNS AND BARRICADES SHALL BE ADJUSTED FO CONDITIONS AS DIRECTED BY THE ENGINEER. THE DIRECTIONAL SHALL BE COVERED OR REMOVED WHEN NO LONGER CONSISTENT W
- C. ADVANCE WARMING SIGNS ARE TO BE OMITTED ON DRIVEWAY UNLI OTHERWISE NOTED.
- D. THE TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS. INTER AND DRIVEWAYS SHALL BE INCIDENTAL TO THE COST OF SPECIFI CONTROL STANDARDS OR ITEMS.

REVISIONS		FI
NAME	DATE	11.
LHA	6/89	TRA
T. RAMMACHER	09/08/94	1177
J. OBERLE	10/18/95	
A. HOUSEH	03/06/96	, T
A. HOUSEH	10/15/96	SI
T. RAMMACHER	01/06/00	
		SCALE
		SUMLE

ILLINOIS DEPARTMENT OF T TRAFFIC CONTROL ANI FOR

SIDE ROADS, INTERSI DRIVEWAY

SCALE: VERT.

HORIZ. DATE 10/18/2002