



* LENESS LN. - LANE WIDTH
VARIES FORM 24' TO 14'

POROUS GRANULAR EMBANKMENT SUBGRADE (PGE) HAS BEEN PROVIDED FOR SOILS WHICH TEND TO BE UNSTABLE WHEN WET. THE ACTUAL NEED FOR REMOVAL AND REPLACEMENT WITH PGE WILL BE DETERMINED IN THE FIELD AT THE TIME OF CONSTRUCTION BY THE ENGINEER (BY USE OF A CONE PENETROMETER IN CONJUNCTION WITH IDOT SUBGRADE MANUAL). IF UNSTABLE SOILS ARE ENCOUNTERED THE SOILS SHALL BE REMOVED AND REPLACED WITH PGE. IF UNSTABLE SOIL IS NOT ENCOUNTERED, THEN THE QUANTITY WILL BE DEDUCTED AND NO ADDITIONAL COMPENSATION WILL BE DUE THE CONTRACTOR.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
575	(B&14) R-3	WILL	390	17
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		
CONTRACT NO. 60961				

- ① EXIST. BITUMINOUS CONCRETE BINDER COURSE
- ② EXIST. BITUMINOUS CONCRETE SURFACE COURSE
- ③ EXIST. P.C. CONCRETE BASE COURSE, 9"
- ④ EXIST. BITUMINOUS BASE COURSE, 1 1/2"
- ⑤ EXIST. BITUMINOUS RESURFACING, 9"
- ⑥ EXIST. BITUMINOUS CONCRETE OVERLAY, 9"
- ⑦ EXIST. P.C. CONCRETE PAVEMENT 9"-6"-9"
- ⑧ EXIST. P.C. CONCRETE PAVEMENT 6"-8"-6"
- ⑨ EXIST. BITUMINOUS CONCRETE SHOULDER
- ⑩ EXIST. AGGREGATE SHOULDERS, TYPE B
- ⑪ EXIST. STABILIZED MEDIAN
- ⑫ EXIST. SUB-BASE GRANULAR MATERIAL, TYPE A
- ⑬ EXIST COMBINATION CURB AND GUTTER, TYPE B-6.12
- ⑭ EXIST COMBINATION CURB AND GUTTER, TYPE B-6.24
- ⑮ EXIST COMBINATION CURB AND GUTTER, TYPE M-6.12
- ⑯ PROP. BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX "C", N50 - 1 1/2"
- ⑰ PROP. POLYMERIZED LEVELING BINDER (MACHINE METHOD), SUPERPAVE, IL-4.75, N-50 - 3/4"
- ⑱ PROP. BITUMINOUS CONCRETE BINDER COURSE, SUPERPAVE, IL-19.0, N50 - 2"
- ⑲ PROP. AGGREGATE SUBGRADE, 12"
- ⑳ PROP. SUB-BASE GRANULAR MATERIAL, TYPE B - 10"
- ㉑ PROP. BITUMINOUS SHOULDERS SUPERPAVE, 6"
- ㉒ PROP. CONCRETE MEDIAN SURFACE, 4 INCH
- ㉓ PROP. CORRUGATED MEDIAN
- ㉔ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12
- ㉕ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24
- ㉖ PROP. BITUMINOUS CONCRETE SURFACE REMOVAL, 2 1/2"
- ㉗ PROP. POLYMERIZED BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX "F", N90 - 1 3/4"
- ㉘ PROP. POLYMERIZED BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX "F", N90 - 1 3/4"
- ㉙ PROP. BITUMINOUS CONCRETE BINDER COURSE, SUPERPAVE, IL-19, N90 - 11"
- ㉚ PROP. STEEL PLATE BEAM GUARD RAIL, TYPE A
- ㉛ PROP. SODDING, SALT TOLERANT OR SEEDING (SEE LANDSCAPING PLAN)
- ㉜ PROP. PERMANENT STEEL SHEET PILING RETAINING WALL
- ㉝ PROP. POROUS GRANULAR EMBANKMENT SUBGRADE

[illegible]

ILLINOIS DEPARTMENT OF TRANSPORTATION

TYPICAL SECTION
US ROUTE 30
SHEET 6 OF 6

SCALE: VERT. NONE
HORIZ. NONE
DATE: 3/1/05

DRAWN BY: SNH
CHECKED BY: KDF

CMT
CRAWFORD MURPHY & TILLY, INC.
CONSULTING ENGINEERS
SPRINGFIELD, IL ■ AURORA, IL ■ ST. LOUIS, MO

Rev. 7-26-05