

TYPICAL BENCHING DETAIL FOR EMBANKMENT

NOTES:

- \bigcirc Construct succeeding bench cuts and embankment placement and compaction from bottom to top in stairstep fashion.
- existing foreslope prepared in accordance with article 205.03 of the standard specifications.
- BENCH CUT EXISTING SLOPE TYPICAL FOR EACH STEP.
- 4 TRIM TO FINAL SLOPE.
- EQUAL 200 (8-INCH) LIFTS OF EMBANKMENT COMPACTED IN ACCORDANCE WITH ARTICLE 205.05 OF THE STANDARD SPECIFICATIONS.
- EXCAVATION OF BENCH CUTS WITHIN EXISTING EMBANKMENT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC METER OR CUBIC YARD FOR "EARTH EXCAVATION". THIS PRICE WILL INCLUDE ALL LABOR AND MATERIAL, NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- 7 SLOPES SHALL BE BENCHED ACCORDING TO THIS DETAIL WHEN THE SLOPE IS STEEPER THAN 4:1 AND THE HEIGHT IS GREATER THAN 5' (1.5)

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN.

REVISIONS DATE		ILLINOIS DEPARTMENT OF TRANSPORTATION	
-			NG DETAIL
		FOR EMBANKMENT WIDENING	
		SCALE: VERT. HORIZ. DATE 4/6/2005	DRAWN BY: CADD
		DATE 4/6/2005	CHECKED BY: S.E.B.
			BD-51

4/6/2005 W:\diststd\bd5i.dgn VI=BD5i

VI=BD5I

501 4/6/2005 10: 35: 34 AV 9587*501886y0198

REVISION DATE: 6-16-2004