









LAP DETAIL III

Pavement Width	Bar Size	Pavement Thickness	(Approx. Spacing)	B	0	0
12 feet	#7	14"	26 spaces (27 bars) @ 5 <sup>1</sup> / <sub>4</sub> "	31/2"	3′′	26''
14 feet	#7	14"	30 spaces (31 bars) @ 53/8"	31/2"	3''	26''
16 feet	#7	14"	35 spaces (36 bars) @ 51/4"	31/2"	3′′	26′′

GENERAL NOTES

- 1. THE PAVEMENT REINFORCEMENT SHALL BE 4.5" FROM THE TOP OF PAVEMENT.
- EXCEPT AS NOTED OR SHOWN, THE DIMENSIONS AND NOTES SPECIFIED FOR LAP DETAIL I ARE TYPICAL FOR LAP DETAIL II AND III.
- 3. THE (B) DIMENSION AND THE DISTANCE FROM THE END OF THE TRANSVERSE BAR TO THE EDGE OF PAVEMENT MAY BE INCREASED BY 1" FOR SLIP FORM PAVING.

CDT-

		001 0		
REVISIONS NAME DATE	ILLINOIS DEPARTMENT OF TRANSPORTATION			
`	F.A.I. 94/90 (DAN RYA	N EXPRESSWAY)		
	31ST STREET TO 71S			
	NB EXPRESS LANE REC	DNSTRUCTION		
	CIVIL DETAILS EXTENDED LANE REINFORCEMENT FOR CONTINUOUSLY REINFORCED PCC PAVEMENT			
	SCALE; NONE	DRAWN BY: TAI		
	DATE: 7/7/06	CHECKED BY, DPR		

Edivards

AND Keicey

ONE NORTH FRANKLIN
CHICAGO, IL 60606
PHONE: (312) 251-3000
FAX: (312) 251-3000
FAX: (312) 251-3000
WEB: WWW.EKCORP.COM