

BUTT JOINT AND

BITUMINOUS TAPER

TYPICAL BUTT JOINT AND BITUMINOUS TAPER
FOR MILLING AND RESURFACING

04/12/2004 w:\diststd\bd32.dgn VI=BD32 BAUERDL

SECTION COUNTY TOTAL SHEET NO 0219 2003-96RS WILL 30 20 62672 PROP. BIT. OR P.C.C.
SURFACE REMOVAL - BUTT JOINT
9.0 m (30ft.) (NOTE "A") SAW CUT (INCLUDED IN THE COST EXIST. BIT. OR OF BITUMINOUS SURFACE CONC. SURFACE 4.5 m (15ft.) (NOTE "B") REMOVAL - BUTT JOINT) (NOTE "D") _45 (1 3/4) FOR E AND F MIX 40 (1 1/2) FOR C AND D MIX * * EXIST. PAVEMENT BUTT JOINT DETAIL TAPER LENGTH * * VARIES PROP. BIT. SURF. CRSE. -PROP. BIT. BINDER CRSE. 45 (1 3/4) FOR E AND F MIX [40 (1 1/2) FOR C AND D MIX * * EXIST. PAVEMENT BITUMINOUS TAPER DETAIL TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR RESURFACING ONLY * * PC CONCRETE, BITUMINOUS OR BITUMINOUS RESURFACED PAVEMENT. NOTES A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS. C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING BITUMINOUS SURFACE. D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED BITUMINOUS COURSES. E: TAPER THE TEMP, RAMP AT A RATE OF 900 (3 ft.) PER INCH OF MILLING THICKNESS. F: INSTALLATION AND REMOVAL OF THE 1.35 m (4.5') TEMP. 8IT. RAMP WILL 8E PAID AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT". G: SEE ARTICLE 406.18 AND 406.24 OF THE STANDARD SPECIFICATIONS FOR "BITUMINOUS AND PCC SURFACE REMOVAL, BUTT JOINT". * SEE TYPICAL SECTIONS FOR MILLING THICKNESS. * * * * 6.1 m (20') PER 25 (1) RESURFACING (NOTE "A") ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS 3.0 m (10') PER 25 (1) RESURFACING (NOTE "B") OTHERWISE SHOWN. ILLINOIS DEPARTMENT OF TRANSPORTATION BASIS OF PAYMENT: BUTT JOINT AND THE BUTT JOINT WILL BE PAID FOR PER SQUARE METER (SQUARE YARD.) AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT" OR AS "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT". BITUMINOUS TAPER DETAILS SCALE: NONE DRAWN BY CHECKED BY

BD400-05 (VI=8D32)

REVISION DATE: 04/06/01