



**GENERAL NOTES:**

- 1.) IT SHALL BE THE RESPONSIBILITY OF THE COUNTY STAFF TO DIVERT THE STREAM FLOW DURING CONSTRUCTION IN ORDER TO KEEP THE CONSTRUCTION AREAS FREE OF WATER. THE METHOD OF WATER DIVERSION SHALL BE SUBJECT TO THE APPROVAL OF THE COUNTY.
- 2.) THE PRECAST CONCRETE CULVERT SECTIONS SHALL BE DESIGNED AND MANUFACTURED IN ACCORDANCE WITH AASHTO M273 (ASTM C1433) WITH LESS THAN 2' OF COVER.
- 3.) FOR BACKFILLING AND EMBANKMENT, SEE STANDARD SPECIFICATIONS.
- 4.) COUNTY TO CONFIRM ALL PRECAST CULVERT DIMENSIONS WITH THE SUPPLIER BEFORE STARTING CONSTRUCTION.
- 5.) SHOP DRAWINGS SHALL BE REQUIRED AND PROVIDED TO THE COUNTY FOR REVIEW.
- 6.) PRECAST CONCRETE BOX CULVERT, 8'x2' (M273) = 61'-6"  
 PRECAST CONCRETE END SECTIONS = 2 EACH  
 TYPE 1 FRAME AND CLOSED LID WITH NECESSARY ADJUSTING RINGS = 2 EACH

CRAWFORD COUNTY  
 FAS ROUTE 694  
 MFT SECTION 03-00088-00-WR

MISCELLANEOUS DETAILS

DRAWN BY MAL	<p>300 N. 3RD. ST., Suite 206      Bismarck, IL 62408      817/842-8888 817/842-8888 fax</p>	FILE NO. 24-7263
DATE 12/29/04		BOOK NO. 2646
CHECKED BY ERB		SHEET NO. 23 OF 56