LIST OF STATE STANDARDS

INDEX OF SHEETS

ARTERIAL ROAD INFORMATION SIGN

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

18

	ST/	ANDARD NO.	DESCRIPTION	
SHEET NO.	DESCRIPTION	000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS	
		442201 -<i>03</i>	CLASS C AND D PATCHES	
1	COVER SHEET	604001 -<i>03</i>	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS LANE CLOSURE, 2L, 2W MOVING OPERATIONS - DAY ONLY URBAN LANE CLOSURE, 2L, 2W UNDIVIDED URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN	
2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES	701301 -<i>04</i>		
3	SUMMARY OF QUANTITIES	701311 <i>-03</i>		
4	TYPICAL SECTIONS PLAN	701501 -06		
5-6	ROADWAY & PAVEMENT MARKINGS PLANS	701606 -<i>0</i>7		
7-8	DETECTOR LOOP REPLACEMENT PLANS	701701 -07		
9	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING	701901-01 TRAFFIC CONTROL DEVICES		
10	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT		TWITTE CONTINUE DEVICES	
11	BUTT JOINT AND HMA TAPER DETAILS			
12	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS			
13	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)			
14	DISTRICT ONE TYPICAL PAVEMENT MARKINGS			
15	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)			
16	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING			

GENERAL NOTES

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES, THE VILLAGE OF LEMONT

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (45 KM/H) OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (45 KM/H), WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V;H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847)705-4470
A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING, EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

-	FILE NAME = .	USER NAME = guillaumefp	DESIGNED	REVISED -
-	c:\pw_work\pwidot\guillaumefp\d0246850\E	110211-sht-plan.dgn	DRAWN -	REVISED -
I		PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
I		PLOT DATE = 5/16/2011	DATE -	REVISED -