TRAFFIC SIGNAL LEGEND

IRELESS ACCESS POINT NAME = USER NAME = bauerd1		SIGNED - DAG/BCK	REVISED	NO. 6 SOLID COPPER (GREEN)					F.A. ·	SECTION	COUNTY TOTA
IRELESS DETECTOR SENSOR	RW B	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED GROUND CABLE IN CONDUIT		~		CROSSING GATE CROSSBUCK		X0X	X0 X - > ≺
AN, TILT, ZOOM CAMERA	PZI	PTZ	PTZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,				FLASHING SIGNAL		X O X	XOX
IDEO DETECTION ZONE	÷R `~			RADIO REPEATER	RERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	2	X OX X	XeX X
IDEO DETECTION CAMERA	R [√¤	(V)	⊙ •	RADIO INTERCONNECT	## * O	##+0		RAILROAD CONTROL CABINET	_		
CROWAVE VEHICLE SENSOR	R M M R		∭	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		() C (3) D	₽ C			EXISTING	PROPOSED_
REFORMED DETECTOR LOOP			Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			×	RAILROAD SYMBOLS			
TECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED						b	<u>+</u> t
LUMINATED SIGN NO RIGHT TURN"	R	8	®	WALK/DON'T WALK SYMBÖL 12" (300mm) PEDESTRIAN SIGNAL HEAD				(SYSTEM) DETECTOR PREFORMED SAMPLING (SYSTEM) DETECTOR		PIS PS	PIS PS
LUMINATED SIGN NO LEFT TURN"	R S	0	•	12" (300mm) PEDESTRIAN SIGNAL HEAD			"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR PREFORMED INTERSECTION AND SAMPLING	OR	PP	· taat
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@aps		"P" INDICATES PROGRAMMED HEAD		(p)	4 Υ 4 G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	OR ,	<u> </u> P	
EDESTRIAN SIGNAL HEAD EDESTRIAN PUSHBUTTON DETECTOR		(i)	⊸	SIGNAL FACE WITH BACKPLATE.		R	R Y G	SAMPLING (SYSTEM) DETECTOR		[5]	S
.ASHER INSTALLATION DENOTES SOLAR POWER)	R ○	O-D ^{"F"}	●-► "F"				 G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[<u>Is</u>]	IS
GNAL HEAD OPTICALLY PROGRAMMED	R -□>"P"	->″P″	→ "P"	SIGNAL FACE			G ← Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
SNAL HEAD WITH BACKPLATE	+CR	+1>	+			R	R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	0-¤		
GNAL HEAD CONSTRUCTION STAGES UMBERS INDICATE THE CONSTRUCTION STAGE)	h		-	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY	RMF		
GNAL HEAD	R		→				[7]	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
TTER) 45 FOOT (13.7m) MINIMUM	⊗ R_	>	>	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	А	R	R	STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O MF		
GNAL POST MPORARY WOOD POLE (CLASS 5 OR	R ○ R ⊗	∘ ⊗	• · ·	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
EEL COMBINATION MAST ARM SEMBLY AND POLE WITH PTZ CAMERA	PTZI	PIZH	PIZ	INTERSECTION ITEM REMOVE ITEM	Đ	I	ΙP	OR (S) SERVICE CONTROLLER CABINET AND	RCF		
SSEMBLY AND POLE WITH LUMINAIRE	"O→X	0- X	•	SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		C	°C∥ ⊢
LUMINUM MAST ARM ASSEMBLY AND POLE TEEL COMBINATION MAST ARM	R	0 7		COMMON TRENCH COILABLE NONMETALLIC CONDUIT (EMPTY)			CT CNC	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)		1— <u>—</u>	-
TEEL MAST ARM ASSEMBLY AND POLE	R O	0		AND CABLE	en e			FIBER OPTIC CABLE NO. 62.5/125,			
ELEPHONE CONNECTION) POLE OR (G) GROUND MOUNT	R	P	P T	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		— <u>(24F</u>)—	-(24F)
ERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	-LR	; - P	<u> </u>	JUNCTION BOX GALVANIZED STEEL CONDUIT			0	FIBER OPTIC CABLE NO. 62.5/125, MM12F		— <u>(12</u> F)—	
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	R DD		X	COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		-6-	-6-
ASTER MASTER CONTROLLER		EMMC	MC	HEAVY DUTY HANDHOLE	R	H	H	VENDOR CABLE FOR CAMERA		—	
OMMUNICATIONS CABINET ASTER CONTROLLER	CC "	E C C	СС	HANDHOLE	R			COMMINE CABLE		7-	
AILROAD CONTROL CABINET				CONFIRMATION BEACON	R_{O-O}	0—()	⊷	COAXIAL CABLE		<u> </u>	<u> </u>
ONTROLLER CABINET	R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	R ⊗<	\bowtie	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		1)—	1