

RHUTASEL and ASSOCIATES, INC. Ð CENTRALIA, ILLINOIS

PREPAR AEC 6005

FREEBURG, ILLINOI

ROUTE NO.	SECTION	COUN	זי	TOTAL SHEETS	SHEET NO.
С.Н. Ю	08-00118-00-BR	FAYETTE		12	8
FEDERAL	AID PROJECT	ILLINOIS	PROJECT	r	

CONTRACT NO. 95662

All field drilled holes shall be coated with an approved zinc rich paint before erection.

All steel rail elements shall be galvanized according to Article 509.05 of the Standard Specifications.

***The studs of the anchor devices shall be placed below the top reinforcement bars and the outermost longitudinal reinforcement bar shall be placed directly above the studs of the rail post anchor device.

The maximum allowable rail post spacing shall be 10'-9". The rail post spacing shown elsewhere in the plans is based on the allowable spacing for another type of rail. When this type of rall is used, the number of posts may be decreased and the post spacing increased to provide equal post spaces of 10'-9" or less.

See Special Provisions for curled end section. The cost of the Curled End Sections shall be included in the contract unit price per foot for "STEEL RAILING, TYPE S1", and no additional compensation will be allowed.



See sheet 5 of 12 for Steel Railing Quantities.

		STEEL RAILING TYPE SI
ARED FOR:	Date: 04/07/2011 Design: WDL Drawn: JSD Job No.: 51410	SECTION 08-00118-00-BR FAYETTE COUNTY STRUCTURE NO. 026-3451