

SEQUENCE OF CONSTRUCTION:

- 1. CLOSE EXISTING VALVE.
- 2. REMOVE EXISTING HYDRANT.
- 3. INSTALL HYDRANT EXTENSION AND NEW VALVE.
- 4. RELOCATE EXISTING HYDRANT.
- 5. OPEN EXISTING VALVE, REMOVE BOX.
- 6. BACKFILL.
- 7. FLUSH AND TEST FOR CHLORIDE RESIDUAL AND PROVIDE TEST.

ALL WORK TO BE DONE IN ACCORDANCE WITH ARTICLE 564 OF THE STANDARD SPECIFICATIONS. NEW VALVE AND BOX SHALL BE SAME MAKE AND MODEL AS EXISTING.

## FIRE HYDRANT TO BE MOVED

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

FILE NAME =	USER NAME = gaglianobt	DESIGNED -	REVISED - R. SHAH 09-09-94		FIRE HYDRANT TO BE MOVED	F.A.P. SECTION	COUNTY TOTAL SHEET
W:\diststd\22x34\bd36.dgn		DRAWN -	REVISED - R. SHAH 10-25-94	STATE OF ILLINOIS	TINE HIDRARI TO BE MOVED	337 20R-4	LAKE 232 181
	PLOT SCALE = 50.0000 ' / IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION		BD-36	CONTRACT NO. 60860
	PLOT DATE = 1/4/2008	DATE -	REVISED -		SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA. TO STA.	FED. ROAD DIST. NO. 1 ILLINOIS FED. A	